



OR-License: Evaluating LLM Agents as Real-World Operations Research Practitioners

Peisong Wang^{1*}, Feixue Liu^{2*}, Yize Meng^{3*}, Bowen Liu^{1,4*}, Ruoyu Chen²,
Gaoyang Dai⁵, Xing He⁶, Aiqian Li⁶, Fengchi Yuan⁷, Aochuan Chen¹,
Chenyi Zi¹, Yuhan Li⁴, Hongchuan Zeng⁴, Yimo Yan⁸, Nuo Chen⁴,
Jie Fu⁹, Zuo-Jun Max Shen², Yong-Hong Kuo^{2†}, and Jia Li^{1,†}

¹HKUST-GZ ²HKU ³Qingzhi Optimization (Jinan) Information Technology Co., Ltd.

⁴Hunyuan, Tencent ⁵XM Capital ⁶Tianjin Meta & Infinite Technology Co., Ltd

⁷CZBANK ⁸American University of Sharjah ⁹Independent Researcher

 [Website](#)

 [Code](#)

 [Dataset](#)

Abstract

Can large language model (LLM) agents deliver expert-level operations research (OR) solutions directly from original client materials, without prior expert reformulation? Existing OR benchmarks commonly begin with self-contained problem descriptions or predefined optimization tasks, leaving the work of translating original business materials into professionally validated solutions underrepresented. We introduce OR-License, an end-to-end benchmark of 31 instances across 10 industrial scenarios drawn from paid OR engagements totaling \$3.68 million in project value. It preserves original requirements, input data, deliverable formats, and information boundaries after de-identification. To evaluate information acquisition throughout optimization, we further introduce ORSim, a controlled client simulator that discloses business facts without supplying OR expertise. Hidden evaluation checks feasibility and compares objective quality against original expert solutions accepted by clients before benchmark construction. Deployment-Adjusted Quality (DAQ) averages expert-relative quality across instances, assigning zero credit to infeasible deliveries. Across 11 frontier LLMs evaluated with coding-agent harnesses, several exceed the expert reference in conditional objective quality, but none matches its DAQ; the strongest primary Claude Code configuration achieves 88.39% strict feasibility and a DAQ of 0.87 against the expert reference of 1. Client information acquisition extends beyond initial clarification into solution development and validation, with some later stages exhibiting higher confirmed issue-resolution proportions. Trajectory analysis identifies failures spanning formulation and implementation, while task-equalized research-chain completion rates range from 24% to 45% across models on evaluable tasks. These findings motivate sustained information-gap resolution, faithful problem formulation, and evidence-linked self-improvement for reliable long-horizon agents.

1 Introduction

Operations research (OR) supports high-value decisions across manufacturing, logistics, healthcare, retail, and many other domains. Deploying an OR system, however, requires experts to transform incomplete business materials into an executable decision process through requirement elicitation, problem formulation, solution strategy selection, and solver implementation. Gurobi’s *State of Mathematical Optimization Report 2024* reports that 82% of survey respondents hold a master’s or doctoral degree (Gurobi Optimization, 2024). We ask whether large language model (LLM) agents can carry out this work.

*Equal contribution.

†Correspondence to: Yong-Hong Kuo<yhkuo@hku.hk> and Jia Li<jialeel@hkust-gz.edu.cn>.




Figure 1: **Three gaps and corresponding improvements in OR-LICENSE.** Each column links an evaluation gap (top) to its improvement (bottom). The client dialogue is illustrative.

Recent work has explored LLMs for OR (Ramamonjison et al., 2023; Huang et al., 2024; Yang et al., 2025; Lu et al., 2025; AhmadiTeshnizi et al., 2024; Li et al., 2025; Chen et al., 2025; Sun et al., 2026), with newer benchmarks extending evaluation to multi-stage agent workflows (Zhou et al., 2026; Li et al., 2026a). However, three important gaps remain in evaluating whether LLMs can take on the work of OR experts in real-world engagements. **Gap 1: Task Complexity and Practical Relevance.** Benchmarks built from academic, synthetic, or reconstructed tasks may not capture the operational complexity and practical demands of real client engagements, limiting what their results reveal about LLMs’ ability to perform professional OR work. **Gap 2: Information Acquisition.** Evaluations that provide the full task context omit the work required to establish that context, a limitation explicitly acknowledged by GDPval (Patwardhan et al., 2025). In real OR engagements, practitioners must identify missing client-held information, ask targeted questions, and integrate the answers throughout problem solving. **Gap 3: Limited Grounding in Professional Delivery.** Professional OR capability requires a reference grounded in the solution quality achieved by experts in real client engagements, alongside correctness checks and algorithmic baselines. Evaluation-specific references can validate task criteria, whereas client-accepted expert deliveries anchor the comparison in outcomes that satisfied real client requirements.

As illustrated in Figure 1, to address these gaps, we introduce OR-LICENSE, an end-to-end benchmark built from real-world OR engagements. The name reflects our focus on the skills required in professional OR practice. OR-LICENSE comprises three core improvements: First, we ground evaluation in original paid industrial OR engagements, preserving realistic requirements, artifacts, and ambiguity after de-identification. Second, we introduce ORSIM, which lets agents acquire client-side business information throughout the workflow while maintaining a boundary between customer knowledge and OR expertise. Third, we evaluate agents against original expert solutions

that were accepted by clients before benchmark construction, providing a realistic reference for professional-quality delivery.

We use OR-LICENSE to investigate three research questions:

RQ1: How do LLM agents compare with OR experts in feasibility and objective quality, and how consistently do they complete evidence-grounded investigations?

RQ2: When do agents acquire client information across the OR workflow, and how does it contribute to confirmed issue resolution?

RQ3: What failure patterns emerge when agents translate business requirements into executable OR solutions, and what capability gaps do they reveal?

The contributions of this work are threefold:

- **A dataset grounded in paid industrial OR engagements.** We curate and release 31 instances across 10 industries, derived from commissioned OR projects representing \$3.68 million in total project value (Section 3.2).
- **An end-to-end evaluation framework for LLM agents as OR practitioners.** We formalize the OR workflow from requirement elicitation to executable decision making and introduce ORSIM, a controlled client simulator that provides business facts throughout formulation, solving, and refinement without supplying OR expertise. We integrate this interaction with coding-agent harnesses and hidden post-submission evaluation of feasibility and expert-relative solution quality (Sections 3.1 and 4).
- **Deployment-oriented metrics and trajectory analysis.** We introduce Deployment-Adjusted Quality (DAQ), averaging expert-relative quality with zero credit for infeasible deliveries, and a Reliability–Quality Profile. Across eleven frontier LLMs, we analyze client information acquisition, failure patterns, and linked cycles of hypothesis formation, experimentation, and revision to relate observed inquiry to delivery performance (Sections 3.4 and 4).

2 Related Work

LLMs for Operations Research. OptiMUS uses a modular agent for mathematical formulation, solver-code generation, and execution-based revision (AhmadiTeshnizi et al., 2024). ORLM, Re-Socratic, and OptMATH improve optimization modeling through specialized training and data synthesis (Huang et al., 2025; Yang et al., 2025; Lu et al., 2025), while ARS generates constraint-aware heuristic code for vehicle-routing variants (Li et al., 2025). Many existing evaluations begin with self-contained problem descriptions or predefined optimization tasks (Ramamonjison et al., 2023; Huang et al., 2024; Yang et al., 2025; Lu et al., 2025). OR-Space and ORAgentBench extend evaluation to multi-file executable environments and multi-stage workflows (Zhou et al., 2026; Li et al., 2026a). OR-LICENSE builds on this direction using original materials from paid industrial engagements, preserving their requirements, data formats, ambiguity, terminology, and information boundaries after de-identification. Agents can query ORSIM throughout formulation, solving, and refinement, making client interaction part of building the executable solution.

Benchmarking LLMs for Professional Work. Recent benchmarks such as GDPval, APEX-Agents, and AgencyBench evaluate economically valuable deliverables and sustained execution across professional tasks and realistic scenarios (Patwardhan et al., 2025; Vidgen et al., 2026; Li et al., 2026b). OR-LICENSE specializes this direction to OR: executable submissions are checked for feasibility against original client requirements, and objective quality is assessed relative to original expert solutions accepted by clients before benchmark construction. Table 8 summarizes the comparison.




Figure 2: **The OR-LICENSE evaluation framework.** Experts curate tasks and reference solutions from real-world OR projects. Agents may query ORSIM throughout problem solving. Final submissions undergo hidden evaluation of feasibility and expert-relative solution quality.

3 Benchmark Construction

In this section, we define the tasks in OR-LICENSE and describe data curation, client interaction through ORSIM, and the evaluation protocol. Figure 2 provides an overview.

3.1 Task Definition

An OR-LICENSE scenario s corresponds to an industry and comprises a set of OR instances $\mathcal{I}_s$. Each instance $i \in \mathcal{I}_s$ defines a concrete OR task with its own decision structure, business rules, objective, and official test cases $c \in \mathcal{C}_i$. For each case c , let $\mathcal{Y}_{i,c}$ denote the decision space, $f_{i,c} : \mathcal{Y}_{i,c} \rightarrow \mathbb{R}$ the objective function, and $\text{verifier}_{i,c}$ a hidden programmatic checker that validates a submitted decision against the task-specific hard constraints and required relationships among decision variables. The underlying optimization problem is

$$\max_{y \in \mathcal{Y}_{i,c}} \sigma_i f_{i,c}(y) \quad \text{subject to} \quad \text{verifier}_{i,c}(y) = \text{pass}, \quad \sigma_i \in \{+1, -1\},$$

where $\sigma_i = +1$ for maximization and $\sigma_i = -1$ for minimization.

For each instance, the agent receives an initial business brief and all task input files, and may query ORSIM for additional client-held business facts throughout formulation, solving, and refinement. It then produces an executable decision $\hat{y}_{i,c} \in \mathcal{Y}_{i,c}$ for each test case c . OR-LICENSE evaluates the feasibility of $\hat{y}_{i,c}$ through $\text{verifier}_{i,c}(\hat{y}_{i,c})$ and its objective quality through $f_{i,c}(\hat{y}_{i,c})$, which is independently recomputed from the agent’s submitted decision.




Figure 3: **Overview of the dataset.** (a): The two-ring donut summarizes the covered industries (outer ring) and OR problem types (inner ring). Industry categories are based on the three-digit subsectors of the 2022 North American Industry Classification System (NAICS) (Office of Management and Budget, 2022), with selected labels shortened for readability. (b): Source-engagement statistics summarize the financial value and human effort associated with the original client projects. (c): The benchmark covers six core OR expert capabilities reflected in the curated tasks.

3.2 Data Curation

We curated 31 instances across 10 industrial scenarios from commissioned OR engagements. Experts with at least three years of professional OR experience de-identified the original requirements, input data, and deliverable formats while preserving the information boundary presented to the agent. They prepared the initial business brief and annotated the client-held facts that could be acquired through ORSIM. Detailed recruitment criteria and curation procedures are provided in Appendix G.

Each instance provides the agent with the de-identified input files and initial brief. Hidden instance-specific verifiers and objective functions evaluate submitted decisions against the original operational requirements, while original expert solutions accepted by the clients provide the reference deliveries. Experts reviewed the consistency among the original project requirements, agent-facing materials, hidden evaluators, and reference solutions. The source engagements represent \$3.68 million in total project value; problem sizes and additional engagement statistics are reported in Appendices G and G.3. Figure 3 summarizes these engagement statistics.

3.3 ORSIM

Real-world OR requirements are often incomplete at the start of a project and may require clarification during formulation, solving, and refinement. We therefore introduce ORSIM, a controlled client-interaction environment that exposes scenario-grounded client facts throughout the episode while withholding OR expertise. Each instance begins with an initial business brief and an expert-reviewed catalog of client facts. The evaluated agent cannot inspect this catalog or the hidden evaluator. Only eligible client-owned facts can be disclosed, while problem formulation, algorithm selection, and solver implementation remain the agent’s responsibility. Each query can disclose at most three non-brief facts.

For each question, a simulator-side LLM selects relevant entries from the closed fact catalog. A deterministic controller validates the selection and enforces the ownership, visibility, and per-query

disclosure rules before passing the authorized text to a response-only LLM for natural-language rendering. The selector and responder do not determine which information may be disclosed. This separation allows flexible semantic matching and language generation while keeping the information boundary programmatic. We evaluate ORSIM with expert-annotated reliability tests; the complete schema, selector variants, disclosure rules, and evaluation protocol are provided in Appendix §C.

3.4 Metrics

A deployable OR solution must satisfy every operational constraint and attain a competitive objective value. These requirements are hierarchical because solution quality has operational meaning only after feasibility is established. We therefore report instance-level feasibility, expert-relative quality, and a feasibility-gated overall score.

Strict Feasibility. For N instances indexed by $i \in \{1, \dots, N\}$, let $\mathcal{C}_i$ be the official test cases of instance i , and let $\hat{y}_{i,c}$ be the final submitted output for case c . An instance is feasible only if every official case passes its hidden verifier:

$$F_i = \mathbf{1}[\forall c \in \mathcal{C}_i, \text{verifier}_{i,c}(\hat{y}_{i,c}) = \text{pass}],$$

$$\text{Feas} = \frac{1}{N} \sum_{i=1}^N F_i. \quad (1)$$

Let $\mathcal{F} = \{i : F_i = 1\}$ and $K = |\mathcal{F}|$.

Expert-Relative Quality. For each $i \in \mathcal{F}$, let J_i^{agent} and J_i^{expert} use the same fixed instance aggregation, and define $\tilde{J}_i^{(\cdot)} = T_i(J_i^{(\cdot)}) > 0$. The instance-specific transformation T_i is strictly increasing and applied identically to the system and expert objectives. We define

$$Q_i = \begin{cases} \frac{\tilde{J}_i^{\text{expert}}}{\tilde{J}_i^{\text{agent}}}, & \text{if instance } i \text{ is a minimization problem,} \\ \frac{\tilde{J}_i^{\text{agent}}}{\tilde{J}_i^{\text{expert}}}, & \text{if instance } i \text{ is a maximization problem.} \end{cases} \quad (2)$$

Here $Q_i = 1$ matches the expert objective, with larger values indicating better solutions. Conditional quality is $Q_{\text{feas}} = K^{-1} \sum_{i \in \mathcal{F}} Q_i$, reported as N/A when $K = 0$. Appendix §A.2 specifies the objective-scale normalization and edge-case conventions.

Deployment-Adjusted Quality. We gate solution quality by setting $Z_i = Q_i$ for $F_i = 1$ and $Z_i = 0$ otherwise. The benchmark-level *Deployment-Adjusted Quality* (DAQ) is

$$\boxed{\text{DAQ} = \frac{1}{N} \sum_{i=1}^N Z_i = \frac{1}{N} \sum_{i \in \mathcal{F}} Q_i} \quad (3)$$

$$= \text{Feas } Q_{\text{feas}} \quad (K > 0).$$

If $K = 0$, $\text{DAQ} = 0$. The expert reference has $\text{DAQ} = 1$.

Reliability-Quality Profile. DAQ is the parameter-free primary metric. To expose how rankings change as evaluation becomes more sensitive to low instance scores, we define the power-mean family (Hardy et al., 1952)

$$\boxed{\text{DAQ}_\alpha = \left(\frac{1}{N} \sum_{i=1}^N Z_i^{1/\alpha} \right)^\alpha} \quad (4)$$

Feas, DAQ, and DAQ_α macro-average over instances, assigning each instance weight $1/N$ regardless of its number of official cases. Here $DAQ_1 = DAQ$, and DAQ_α is monotonically nonincreasing in α . Larger α values penalize low instance-level scores, including incomplete and uneven delivery, more strongly. Appendix §A.4 gives the decomposition, monotonicity argument, and compensation analysis.

We use DAQ as the primary score and evaluate the reliability-quality profile at $\alpha \in \{1.0, 1.1, \dots, 3.0\}$, a pre-specified grid of 21 values with step size 0.1.

3.5 Trajectory Analysis Methodology

Final-delivery scores do not reveal how agents acquire information, repair errors, or conduct evidence-linked revisions. We therefore manually annotate three observable dimensions of each retained trajectory using task materials, interaction logs, execution feedback, and final artifacts. The complete coding and aggregation protocol is given in Appendix §B.

For client information acquisition, we assign each ask action to one of six OR workflow stages: before solver code (S1), before solver feedback (S2), before the first candidate (S3), before a complete candidate (S4), before the self-check passes (S5), and before final submission (S6). We also record whether the agent asks again after solving feedback when another decision opportunity remains.

For scientific inquiry, we annotate research opportunities: consequential uncertainties visible to the agent and potentially reducible through investigation. For each opportunity, we identify a testable hypothesis (H), a mechanistic explanation (C), an executed diagnostic experiment (A), evidence interpretation (E), and an evidence-grounded update (U). A complete HCAEU chain links these behaviors within the same issue and branch: H and C precede A, the experimental result informs E, and E leads to U. We report chain completion and, among opportunities with a complete chain, stage quality based on a three-level rubric. The rubric and aggregation rules are given in Appendix B.

For trajectory-level error analysis, we identify confirmed error events from the agent trajectory and final artifact and classify each event by its point of origin. We use eight categories: problem understanding (UND), data and parameter mapping (DATA), decision representation (DEC), static constraints (CON), dynamic and state transitions (DYN), uncertainty and information structure (UNC), objective and preference formulation (OBJ), and implementation and delivery (IMP). Because a trajectory may contain multiple error events, category profiles are computed at the event level, with infeasible rates reported separately.

4 Evaluation

We evaluate eleven frontier models on the three research questions introduced in Section 1, with five runs per model–task pair. Feasibility and DAQ first average the five runs within each task, then weight the 31 task means equally. Their reported spreads are the arithmetic means of the within-task sample standard deviations; conditional quality and its spread divide the DAQ mean and spread by the observed mean feasibility. These spreads describe within-task variation, not standard errors of the benchmark mean. Reliability–quality profiles apply the same task-equal averaging to $Z^{1/\alpha}$ before raising the result to α .


We further analyze agents’ solution techniques, objective handling, and problem-structure exploitation in comparison with expert reference solutions in Appendix §E.

The complete model list, prompt templates, evaluation settings, and the average cost of each agent are provided in Appendix §D.

Execution setup. We use Claude Code as the primary evaluation harness and expose ORSIM through the Bash command `ask`. This provides a common shell-based interface for model execution while keeping client interaction within the benchmark protocol. An additional Codex harness

Table 1: Main results under Claude Code on 31 tasks with five runs per model–task pair (%). Means weight tasks equally. For feasibility and DAQ, $\pm$ reports the mean within-task sample standard deviation; quality and its spread are DAQ and its spread divided by mean feasibility. Right: task-equal reliability–quality profiles; the expert reference is 1.

Model	Claude Code		
	Feasibility (%)	Quality (%)	DAQ (%)
🔥 Claude Opus 5 (xhigh)	77.42 $\pm$ 4.98	100.03 $\pm$ 9.38	77.44 $\pm$ 7.26
🦋 DeepSeek-V4.1-Flash (high)	69.68 $\pm$ 14.60	99.44 $\pm$ 22.86	69.28 $\pm$ 15.93
📊 Doubao-Seed-2.1-Pro (high)	65.16 $\pm$ 17.81	99.47 $\pm$ 28.34	64.82 $\pm$ 18.47
🌟 Gemini 3.8 Flash (high)	82.58 $\pm$ 17.49	100.43 $\pm$ 23.07	82.94 $\pm$ 19.06
📋 GLM-5.3-Flash (max)	62.58 $\pm$ 25.35	101.01 $\pm$ 41.04	63.21 $\pm$ 25.68
📋 GPT-5.6 Sol (xhigh)	84.52 $\pm$ 17.02	100.59 $\pm$ 21.04	85.02 $\pm$ 17.78
🌀 Grok 4.6 (high)	88.39 $\pm$ 10.28	97.92 $\pm$ 14.67	86.55 $\pm$ 12.97
🌀 Hy3 (high)	45.16 $\pm$ 19.58	96.92 $\pm$ 43.18	43.77 $\pm$ 19.50
🌀 Hy4 preview (high)	66.45 $\pm$ 9.95	100.61 $\pm$ 15.62	66.85 $\pm$ 10.38
🌀 Muse Spark 1.3 (high)	74.19 $\pm$ 12.04	98.21 $\pm$ 16.63	72.86 $\pm$ 12.34
🌀 Qwen3.8-Max (xhigh)	78.71 $\pm$ 23.11	99.06 $\pm$ 30.13	77.97 $\pm$ 23.71



comparison is reported in Appendix D.7. Complete model versions, execution budgets, prompts, and instance-specific settings are provided in Appendices D and G.

4.1 RQ1: Cross-Model Comparison and Performance Against Human Experts

Metric-based results. Table 1 shows that the models differ more in whether they complete a feasible delivery than in their conditional objective quality. Feasibility spans 43.23 percentage points, from 45.16% for Hy3 to 88.39% for Grok 4.6, whereas conditional quality spans only 4.09 points, from 96.92% to 101.01%. These quality scores concern model-specific feasible subsets, however, and do not establish comparable optimization capability across all instances.

Several models exceed the expert quality reference of 100% on their feasible deliveries, but DAQ places every model below the expert. Grok 4.6 achieves the highest DAQ in the primary comparison at 86.55%, leaving a 13.45-point gap. Using $DAQ = Feas \cdot Q_{feas}$, this gap decomposes into 11.61 points from infeasible deliveries and 1.84 points from the net objective shortfall on feasible ones. Thus, approximately 86% of its score deficit comes from the zero credit assigned to failed deliveries. **The dominant observed gap is therefore incomplete feasible delivery, rather than modest objective shortfalls on successful cases.**

The reliability–quality profile in the right panel of Table 1 reinforces this distinction. Increasing α reduces the compensation that high-scoring instances provide for low-scoring or infeasible ones. All eleven models retain the same ranking across the 21 plotted values from 1 to 3, while their scores decrease and remain below the expert reference. The observed ordering is therefore stable across the tested reliability penalties, but no model closes the expert gap.

Trajectory-based results. Following Section 3.5, Figure 4 summarizes stopping locations along the HCAEU chain (left) and compares stage quality conditional on a complete chain against model-average DAQ (right).

Task-equalized complete-chain proportions range from 24% for Muse Spark 1.3 to 45% for Grok 4.6, remaining below 50% for every model. The stopping locations reveal distinct gaps in initiating investigations, testing explanations, and acting on evidence. GPT-5.6 Sol forms no testable hypothesis in 41% of opportunities, whereas Qwen3.8-Max stops at HC and HCAE in 21% each. In particular, stopping at HCAE indicates that evidence has been interpreted without a linked, evidence-grounded update. **Producing an explanation or interpreting a result is therefore distinct from using that**




Figure 4: Research-chain analysis for RQ1. (a) Task-equalized stopping locations along the HCAEU chain. (b) Mean stage quality among opportunities with a complete HCAEU chain versus model-average DAQ.




Figure 5: Left: question timing by workflow stage. Segment width shows the task-equalized question share; height shows the pooled proportion with confirmed issue resolution. Right: bar length shows the infeasible rate from Table 1; colored segments show the fixed annotated error-event distribution, scaled to that length. A trajectory may contain multiple events.

evidence to revise the working hypothesis or solution. These are gaps in observable research-chain completion, not proof that every incomplete chain leaves its issue unsolved.

Conditional stage quality and DAQ also yield different model rankings. GPT-5.6 Sol combines a DAQ of 85.02% with relatively low conditional stage quality, whereas Qwen3.8-Max has the highest conditional stage quality but a lower DAQ of 77.97%. Moreover, Qwen3.8-Max completes the chain in only 27% of research opportunities. **High research quality within completed investigations does not imply that a model can consistently sustain such investigations across research opportunities.** These findings reveal a key limitation of current agents: **they can occasionally demonstrate strong evidence-based reasoning, but still lack the reliability to carry investigations from uncertainty to evidence-grounded revision throughout long-horizon OR problem solving.** Final-delivery performance and sustained research capability therefore represent distinct dimensions of expertise that must be evaluated separately.

4.2 RQ2: Client Information Acquisition Across the OR Workflow

The left panel of Figure 5 summarizes the timing and confirmed issue resolution of classifiable pre-submission client questions. We assign questions to S1–S6 relative to solver-code development, observed feedback, candidate construction, self-checking, and final submission. Segment width denotes the task-equalized question share, and height the pooled confirmed-resolution proportion. Resolution requires a concrete issue, targeted action, and confirming outcome; ordinary rule requests and unresolved or unknown outcomes remain in the denominator when their stage is known.

Questioning is strongly front-loaded: S1 accounts for 86.7%–98.3% of questions across models. Even for Hy4 Preview and GPT-5.6 Sol, only approximately 13% of questions occur after S1, compared with 9% for DeepSeek-V4.1-Flash. Later questions appear across different stages, including S3–S5, but constitute a small fraction of total interaction. **Despite having access to client information throughout the workflow, agents predominantly treat information acquisition as an initial requirement-gathering activity, rather than consistently revisiting their understanding as solution development proceeds.**

Later-stage interactions nevertheless contribute to confirmed issue resolution. Confirmed-resolution proportions range from 10.6% to 37.0% in S1, compared with approximately 56% for DeepSeek-V4.1-Flash in S4 and 71% for Hy4 Preview in S5. At S4, an initial candidate already exists; at S5, a complete candidate has been constructed but has not yet passed self-checking. **These observations show that client clarification can support the diagnosis and correction of concrete issues after solution construction has begun, rather than serving only to establish the initial specification.**

Taken together, these results reveal a gap between continuous access to client information and its sustained use during problem solving. Agents can resolve specific issues through later clarification, yet their information-seeking behavior remains heavily concentrated before substantive solver development. **A key limitation of current agents is the lack of a consistent, feedback-responsive process for identifying and resolving information gaps as solutions evolve.** Reliable end-to-end OR agents should be able to recognize when intermediate results or execution feedback warrant revisiting business assumptions, seek targeted clarification, and incorporate the acquired facts into verified revisions of the formulation or implementation.

4.3 RQ3: LLM Failure Patterns in End-to-End OR Projects

Within the annotated trajectories, formulation errors are prominent across models (Figure 5, right): implementation and delivery (IMP) is the largest error category for only two of the eleven models. Static constraint errors (CON) account for 42.7% of Claude Opus 5’s error events, while dynamic and state-transition errors (DYN) account for 28.7% and 25.5% of those for Hy4 Preview and GLM-5.3-Flash, respectively. Objective and preference formulation (OBJ) and uncertainty and information structure (UNC) together account for 69.0% of Grok 4.6’s error events and 70.5% of Muse Spark 1.3’s. These profiles identify what requires correction, rather than providing an additive attribution of each model’s failure probability.

The distinction is between *solving a specified optimization problem* and *formulating the right problem from business requirements*. An executable program may faithfully implement a formulation that misrepresents the required objectives, state transitions, or information structure; improving execution alone would not correct that mismatch. Meanwhile, IMP remains the largest category for GPT-5.6 Sol and Hy3 (33.3% and 33.1%), so implementation failures also persist. Read alongside RQ1 and RQ2, these findings motivate agents that use both experimental evidence and client facts to revisit their task interpretation and revise the adopted solution. **The central requirement is not merely runnable code or plausible numerical outputs, but consistency from business semantics through formulation, implementation, and validation.**

5 Conclusion

OR-LICENSE evaluates LLM agents on 31 de-identified OR instances from 10 industrial scenarios using original client materials, ORSIM-mediated interaction, hidden feasibility checks, and client-accepted expert references. Across eleven evaluated models, several exceed the expert-normalized objective-quality reference on feasible instances, yet none matches the expert reference in Deployment-Adjusted Quality. Trajectory analysis shows that information acquisition continues beyond initial clarification into solution development and validation; for some models, later-stage questions are associated with higher confirmed issue-resolution proportions. These findings motivate better requirement interpretation, formulation, validation, sustained information-gap resolution, and evidence-linked self-improvement.

AI Use Statement

We used generative AI tools to assist with translation, dataset cleaning and reformatting, qualitative and thematic data analysis, scientific figure presentation, manuscript editing, software development, and literature discovery.

All AI-assisted outputs, including reformatted datasets, qualitative and thematic analyses, code used for generating or refining figures, manuscript text, and references, were reviewed and verified for correctness by four human reviewers. We take responsibility for the final content of this work, including any text, claims, code, data, figures, references, analyses, or other artifacts produced with the aid of generative AI.

References

- Yelaman Abdullin, Diego Molla, Bahadorreza Ofoghi, Vicky Mak-Hau, and John Yearwood. Can an llm elicit information from users in simple optimization modelling dialogues? In *Proceedings of the 23rd Annual Workshop of the Australasian Language Technology Association*, pp. 64–75, 2025.
- Ali AhmadiTeshnizi, Wenzhi Gao, and Madeleine Udell. Optimus: Scalable optimization modeling with (mi) lp solvers and large language models. *arXiv preprint arXiv:2402.10172*, 2024.
- Alibaba Group. Alibaba unveils qwen3.8-max: Its largest and most capable flagship model to date. Alibaba Group Newsroom, August 2026. URL <https://alihome.alibaba-inc.com/en-US/document-2021044032125272064>. Accessed: 2026-09-14.
- Anthropic. Introducing claude opus 5. Anthropic News, July 2026. URL <https://www.anthropic.com/news/claude-opus-5>. Accessed: 2026-09-14.
- ByteDance Seed Team. Seed2.1 officially released: Advancing ai productivity. ByteDance Seed Blog, June 2026. URL <https://seed.bytedance.com/en/blog/seed2-1-officially-released-advancing-ai-productivity>. Accessed: 2026-09-24.
- Ruisheng Cao, Mouxiang Chen, Jiawei Chen, Zeyu Cui, Yunlong Feng, Binyuan Hui, Yuheng Jing, Kaixin Li, Mingze Li, Junyang Lin, et al. Qwen3-coder-next technical report. *arXiv preprint arXiv:2603.00729*, 2026.
- Brian J Chan, Chao-Ting Chen, Jui-Hung Cheng, and Hen-Hsen Huang. Don’t do rag: When cache-augmented generation is all you need for knowledge tasks. In *Companion proceedings of the ACM on web conference 2025*, pp. 893–897, 2025.
- Hongzheng Chen, Yingheng Wang, Yaohui Cai, Hins Hu, Jiajie Li, Shirley Huang, Chenhui Deng, Rongjian Liang, Shufeng Kong, Haoxing Ren, Samitha Samaranayake, Carla P. Gomes, and Zhiru Zhang. Heurigym: An agentic benchmark for llm-crafted heuristics in combinatorial optimization. *arXiv preprint arXiv:2506.07972*, 2025.
- Tong Chen, Hongwei Wang, Sihao Chen, Wenhao Yu, Kaixin Ma, Xinran Zhao, Hongming Zhang, and Dong Yu. Dense x retrieval: What retrieval granularity should we use? In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, pp. 15159–15177, 2024.
- DeepSeek. Deepseek-v4.1-flash: Smarter, faster, more efficient. DeepSeek API Documentation, September 2026. URL <https://api-docs.deepseek.com/news/news260910/>. Accessed: 2026-09-24.
- Yaqi Duan, Yichun Hu, and Jiashuo Jiang. Ask, clarify, optimize: Human-llm agent collaboration for smarter inventory control. *arXiv preprint arXiv:2601.00121*, 2025.
- Darren Edge, Ha Trinh, Newman Cheng, Joshua Bradley, Alex Chao, Apurva Mody, Steven Truitt, Dasha Metropolitansky, Robert Osazuwa Ness, and Jonathan Larson. From local to global: A graph rag approach to query-focused summarization. *arXiv preprint arXiv:2404.16130*, 2024.

- Shahul Es, Jithin James, Luis Espinosa Anke, and Steven Schockaert. Ragas: Automated evaluation of retrieval augmented generation. In *Proceedings of the 18th conference of the european chapter of the association for computational linguistics: system demonstrations*, pp. 150–158, 2024.
- Jyotheesh Gaddam, Lele Zhang, Vicky Mak-Hau, John Yearwood, Bahadorreza Ofoghi, and Diego Molla-Aliod. Agentmilo: a knowledge-based framework for complex milp modelling conversations with llms. In *2025 17th International Conference on Computer and Automation Engineering (ICCAE)*, pp. 176–182. IEEE, 2025.
- Google. Gemini 3.8 flash. Gemini API Documentation, 2026. URL <https://ai.google.dev/gemini-api/docs/models/gemini-3.8-flash/>. Accessed: 2026-09-24.
- Gurobi Optimization. State of mathematical optimization report 2024, 2024. URL <https://www.gurobi.com/resources/report-state-of-mathematical-optimization-2024/>.
- Godfrey Harold Hardy, John Edensor Littlewood, and George Pólya. *Inequalities*. Cambridge university press, 1952.
- Frederick S Hillier, Gerald J Lieberman, Karl Schmedders, Molly Stephens, Mark Hillier, and Michael O'Sullivan. *Introduction to operations research*, volume 9. McGraw-Hill New York, 1995.
- Bo Huang, Fengxiang Li, Hao Xu, Haoyang Huang, Hongyi Fu, Jinhua Hao, Kun Yuan, Minglei Zhang, Pengcheng Xu, Shiyang Liu, et al. Kat-coder-v2. 5 technical report. *arXiv preprint arXiv:2607.05471*, 2026.
- Chenyu Huang, Zhengyang Tang, Shixi Hu, Ruoqing Jiang, Xin Zheng, Dongdong Ge, Benyou Wang, and Zizhuo Wang. Orlm: A customizable framework in training large models for automated optimization modeling. *Operations Research*, 73(6):2986–3009, 2025.
- Xuhan Huang, Qingning Shen, Yan Hu, Anningzhe Gao, and Benyou Wang. Llm for mathematical modeling: Towards bridging the gap between natural and mathematical languages. *arXiv preprint arXiv:2405.13144*, 2024.
- Yuki Imajuku, Kohki Horie, Yoichi Iwata, Kensho Aoki, Naohiro Takahashi, and Takuya Akiba. ALE-bench: A benchmark for long-horizon objective-driven algorithm engineering. In *The Thirty-ninth Annual Conference on Neural Information Processing Systems Datasets and Benchmarks Track*, 2025. URL <https://openreview.net/forum?id=JCjGvbsOmQ>.
- David Klahr and Kevin Dunbar. Dual space search during scientific reasoning. *Cognitive science*, 12(1):1–48, 1988.
- Klaus Krippendorff. Computing krippendorff’s alpha-reliability. 2011.
- Jiajun Li, Mingshu Cai, Yixuan Li, Yu Ding, Ran Hou, Guanyu Nie, Xiongwei Han, and Wanyuan Wang. Oragentbench: Can llm agents solve challenging operations research tasks end to end? *arXiv preprint arXiv:2606.19787*, 2026a.
- Kai Li, Fei Liu, Zhenkun Wang, Xialiang Tong, Xiongwei Han, Mingxuan Yuan, and Qingfu Zhang. Ars: Automatic routing solver with large language models. *arXiv preprint arXiv:2502.15359*, 2025.
- Keyu Li, Junhao Shi, Yang Xiao, Mohan Jiang, Jie Sun, Yunze Wu, Dayuan Fu, Shijie Xia, Xiaojie Cai, Tianze Xu, Weiye Si, Wenjie Li, Dequan Wang, and Pengfei Liu. AgencyBench: Benchmarking the frontiers of autonomous agents in 1M-token real-world contexts. *arXiv preprint arXiv:2601.11044*, 2026b. doi: 10.48550/arXiv.2601.11044. URL <https://arxiv.org/abs/2601.11044>. Accepted to ACL 2026 Main Conference.
- Zhuowan Li, Cheng Li, Mingyang Zhang, Qiaozhu Mei, and Michael Bendersky. Retrieval augmented generation or long-context llms? a comprehensive study and hybrid approach. In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing: Industry Track*, pp. 881–893, 2024.

- Hongliang Lu, Zhonglin Xie, Yaoyu Wu, Can Ren, Yuxuan Chen, and Zaiwen Wen. Optmath: A scalable bidirectional data synthesis framework for optimization modeling. In *International Conference on Machine Learning*, 2025.
- Meta. Models: Muse spark 1.3. Meta Model API Documentation, 2026. URL <https://dev.meta.ai/docs/models>. Accessed: 2026-09-24.
- Bharath Sivaram Narasimhan and Karthik R Narasimhan. τ -rec: A verifiable benchmark for agentic recommender systems. *arXiv preprint arXiv:2606.10156*, 2026.
- Office of Management and Budget. *North American Industry Classification System: United States*, 2022. Executive Office of the President, 2022. URL https://www.census.gov/naics/reference_files_tools/2022_NAICS_Manual.pdf.
- OpenAI. Gpt-5.6: Frontier intelligence that scales with your ambition. OpenAI, July 2026a. URL <https://openai.com/index/gpt-5-6/>. Accessed: 2026-09-14.
- OpenAI. GPT-6 Astra System Card. OpenAI Deployment Safety Hub, September 2026b. URL <https://deploymentsafety.openai.com/gpt-6-astra>. Accessed: 2026-09-13.
- Krista Opsahl-Ong, Arnav Singhvi, Jasmine Collins, Ivan Zhou, Cindy Wang, Ashutosh Baheti, Owen Oertell, Jacob Portes, Sam Havens, Erich Elsen, et al. Officeqa pro: An enterprise benchmark for end-to-end grounded reasoning. *arXiv preprint arXiv:2603.08655*, 2026.
- Tejal Patwardhan, Rachel Dias, Elizabeth Proehl, Grace Kim, Michele Wang, Olivia Watkins, Simón Posada Fishman, Marwan Aljubeh, Phoebe Thacker, Laurance Fauconnet, et al. Gdp-val: Evaluating ai model performance on real-world economically valuable tasks. *arXiv preprint arXiv:2510.04374*, 2025.
- Margus Pedaste, Mario Mäeots, Leo A Siiman, Ton De Jong, Siswa AN Van Riesen, Ellen T Kamp, Constantinos C Manoli, Zacharias C Zacharia, and Eleftheria Tsourlidaki. Phases of inquiry-based learning: Definitions and the inquiry cycle. *Educational research review*, 14:47–61, 2015.
- Rindranirina Ramamonjison, Timothy T. Yu, Raymond Li, Haley Li, Giuseppe Carenini, Bissan Ghaddar, Shiqi He, Mahdi Mostajabdeh, Amin Banitalebi-Dehkordi, Zirui Zhou, and Yong Zhang. Nl4opt competition: Formulating optimization problems based on their natural language descriptions. In *Proceedings of the NeurIPS 2022 Competitions Track*, Proceedings of Machine Learning Research, 2023.
- Sudha Rao and Hal Daumé III. Learning to ask good questions: Ranking clarification questions using neural expected value of perfect information. In *Proceedings of the 56th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 2737–2746, 2018.
- Parth Sarthi, Salman Abdullah, Aditi Tuli, Shubh Khanna, Anna Goldie, and Christopher Manning. Raptor: Recursive abstractive processing for tree-organized retrieval. In *International Conference on Learning Representations*, volume 2024, pp. 32628–32649, 2024.
- Weiwei Sun, Shengyu Feng, Shanda Li, and Yiming Yang. Co-bench: Benchmarking language model agents in algorithm search for combinatorial optimization. In *Proceedings of the AAAI Conference on Artificial Intelligence*, 2026.
- Jianheng Tang, Qifan Zhang, Yuhan Li, Nuo Chen, and Jia Li. Grapharena: Evaluating and exploring large language models on graph computation. In *International Conference on Learning Representations*, volume 2025, pp. 48118–48145, 2025.
- Tencent. Tencent hunyuan officially releases hy3, advancing agent capabilities and deeper product integration. Tencent News, July 2026a. URL <https://www.tencent.com/tencent-hunyuan-officially-releases-hy3-advancing-agent-capabilities-and-deeper-product-integration/>. Accessed: 2026-09-24.

- Tencent. Tencent releases and open-sources tencent hy4 preview. Tencent News, 2026b. URL <https://www.tencent.com/tencent-releases-and-open-sources-tencent-hy4-preview/>. Accessed: 2026-09-14.
- Joseph Tso, Preston Schmittou, Quan Huynh, and Jibran Hutchins. Constraintbench: Benchmarking llm constraint reasoning on direct optimization. *arXiv preprint arXiv:2602.22465*, 2026.
- Bertie Vidgen, Austin Mann, Abby Fennelly, John Wright Stanly, Lucas Rothman, Marco Burstein, Julien Benchek, David Ostrofsky, Anirudh Ravichandran, Debnil Sur, Neel Venugopal, Alannah Hsia, Isaac Robinson, Calix Huang, Olivia Varones, Daniyal Khan, Michael Haines, Austin Bridges, Jesse Boyle, Koby Twist, Zach Richards, Chirag Mahapatra, Brendan Foody, and Osvald Nitski. APEX-Agents. *arXiv preprint arXiv:2601.14242*, 2026. doi: 10.48550/arXiv.2601.14242. URL <https://arxiv.org/abs/2601.14242>.
- xAI. Introducing grok 4.6. xAI News, 2026. URL <https://x.ai/news/grok-4-6>. Accessed: 2026-09-14.
- Anyi Xu, Bangcai Lin, Bing Xue, Bingxuan Wang, Bingzheng Xu, Bochao Wu, Bowei Zhang, Chaofan Lin, Chen Dong, Chenchen Ling, et al. Deepseek-v4: Towards highly efficient million-token context intelligence. *arXiv preprint arXiv:2606.19348*, 2026.
- Zhicheng Yang, Yiwei Wang, Yinya Huang, Zhijiang Guo, Wei Shi, Xiongwei Han, Liang Feng, Linqi Song, Xiaodan Liang, and Jing Tang. Optibench meets resocratic: Measure and improve LLMs for optimization modeling. In *The Thirteenth International Conference on Learning Representations*, 2025. URL <https://openreview.net/forum?id=fsDZwS49uY>.
- Shunyu Yao, Noah Shinn, Pedram Razavi, and Karthik Narasimhan. τ -bench: A benchmark for tool-agent-user interaction in real-world domains, 2024. URL <https://arxiv.org/abs/2406.12045>.
- Z.AI. Glm-5.3-flash: More intelligence with less compute. AutoClaw Blog, September 2026. URL <https://autoclave.z.ai/blog/model/glm-5.3-flash/>. Accessed: 2026-09-24.
- Chenyu Zhou, Xinyun Lu, Jiangyue Zhao, Jianghao Lin, Dongdong Ge, and Yinyu Ye. OR-Space: A full-lifecycle workspace benchmark for industrial optimization agents. *arXiv preprint arXiv:2605.28158*, 2026.

Appendix Contents

A Metric Definitions and Analysis	17
A.1 Instance-Level Feasibility and Aggregation	17
A.2 Objective Normalization and Expert-Relative Quality	17
A.3 DAQ Properties	17
A.4 Reliability-Quality Profile	18
B Trajectory Analysis Protocol	18
C Details and Reliability of ORSIM	20
C.1 Simulator Architecture and Selector Variants	20
C.2 Reliability Analysis	21
D Implementation Details	26
D.1 Agent Harness Selection	26
D.2 Models	27
D.3 Settings	27
D.4 Semantic Validation	27
D.5 Prompts	28
D.6 Agent Resource Usage	40
D.7 Harness Ablation	40
E Solution Strategies and Optimization-Structure Exploitation	41
E.1 Annotation Framework	41
E.2 Strategy Patterns and Expert Comparison	42
F Extended Comparison with Related Benchmarks	45
G Dataset Details	47
G.1 Expert Recruitment and Task Construction	47
G.2 Task Quality Control	48
G.3 Problem Sizes	48
G.4 Verification, Evaluation, and Competency Coverage	48

A Metric Definitions and Analysis

This appendix gives the normalization rules, edge-case conventions, and analytical properties of the metrics introduced in Section 3.4.

A.1 Instance-Level Feasibility and Aggregation

Each instance represents one deployment-level delivery and may contain multiple official test cases. The indicator F_i in Equation (1) equals one only when the final submission passes the hidden verifier on every official case. A submission that passes a strict subset of the cases has $F_i = 0$. This all-cases criterion reflects the delivery requirement that one solver implementation must satisfy the operational constraints throughout the instance.

The fixed-denominator metrics Feas, DAQ, and DAQ_α use an instance-level macro-average. Every instance receives weight $1/N$, irrespective of $|\mathcal{C}_i|$. Official instances determine the strict feasibility decision and the within-task objective aggregation, while the cross-instance weight remains fixed. With $\mathcal{F} = \{i : F_i = 1\}$ and $K = |\mathcal{F}|$, Strict Feasibility is $\text{Feas} = K/N$.

A.2 Objective Normalization and Expert-Relative Quality

For each feasible instance, J_i^{agent} and J_i^{expert} denote the instance-level objective values of the final system submission and the expert reference solution. Both use the same hidden objective and the same fixed aggregation over $\mathcal{C}_i$. Ratio-based comparison requires a strictly positive scale. When the raw objective is strictly positive, T_i is the identity map. Otherwise, the benchmark applies an instance-specific transformation

$$\tilde{J}_i = T_i(J_i) > 0,$$

where T_i is positive on the evaluated objective domain, applied identically to every system and the expert reference, and strictly increasing to preserve the original objective ordering. Equation (2) then uses $\tilde{J}_i$ for both minimization and maximization instances.

For Tasks 21 and 22, the economic objective is cumulative return R , which is maximized, and the stored evaluation cost is $C = -R$. We use the terminal net asset value factor $T(R) = 1 + R = 1 - C$, giving $Q_i = (1 - C_i^{\text{agent}})/(1 - C_i^{\text{expert}})$. All reported scores for these two tasks use this normalization. Feasibility follows the verifier outcome independently of objective sign. A passed run with a missing or nonpositive net asset value factor is explicitly flagged as a scoring error while retaining its verifier-assigned feasibility status.

The expert-relative score has a common interpretation across instances: $Q_i = 1$ matches the expert objective, $Q_i > 1$ improves on it, and $Q_i < 1$ falls below it. The transformation makes the ratio dimensionless and anchors every instance at the expert value of one under the benchmark’s fixed scaling protocol.

The conditional average $Q_{\text{feas}} = K^{-1} \sum_{i \in \mathcal{F}} Q_i$ measures solution quality after successful delivery. When $K = 0$, Q_{feas} is undefined and reported as N/A. Since $\mathcal{F}$ varies across systems, Q_{feas} serves as a diagnostic metric. DAQ provides the fixed-denominator overall ranking.

A.3 DAQ Properties

The gated instance score Z_i defined in Section 3.4 assigns objective quality only to complete deliveries. Therefore an infeasible instance receives zero deployment-adjusted quality even when its raw

objective value appears favorable. Starting from Equation (3), for $K > 0$,

$$\begin{aligned} \text{DAQ} &= \frac{1}{N} \sum_{i \in \mathcal{F}} Q_i \\ &= \frac{K}{N} \left(\frac{1}{K} \sum_{i \in \mathcal{F}} Q_i \right) \\ &= \text{Feas } Q_{\text{feas}}, \end{aligned} \tag{5}$$

which establishes the final equality in Equation (3). If $K = 0$, every $Z_i = 0$, so $\text{DAQ} = 0$ while Q_{feas} remains N/A. For the expert reference, $F_i = Q_i = Z_i = 1$ for every instance, giving $\text{DAQ}_{\text{expert}} = 1$.

A.4 Reliability-Quality Profile

DAQ is the arithmetic mean of the instance scores Z_i , so quality gains on completed instances can compensate linearly for incomplete instance coverage. Since Q_i has no explicit upper cap, a small number of high-quality solutions can offset failures on other instances. Equation (4) exposes this trade-off through a power mean of order $1/\alpha$.

At $\alpha = 1$, the profile recovers the primary metric:

$$\text{DAQ}_1 = \frac{1}{N} \sum_{i=1}^N Z_i = \text{DAQ}.$$

For $\alpha_2 > \alpha_1 \geq 1$, the corresponding power-mean orders satisfy $1/\alpha_2 < 1/\alpha_1$. The power-mean inequality therefore gives

$$\text{DAQ}_{\alpha_2} \leq \text{DAQ}_{\alpha_1}. \tag{6}$$

Increasing α raises sensitivity to low instance scores. This strengthens the penalty on infeasible instances, for which $Z_i = 0$, and on uneven quality among feasible instances. The expert reference satisfies $\text{DAQ}_\alpha = 1$ for every $\alpha \geq 1$.

For $K > 0$, define the conditional power mean

$$Q_{\text{feas},\alpha} = \left(\frac{1}{K} \sum_{i \in \mathcal{F}} Q_i^{1/\alpha} \right)^\alpha.$$

The profile then decomposes as

$$\boxed{\text{DAQ}_\alpha = \text{Feas}^\alpha Q_{\text{feas},\alpha}}. \tag{7}$$

If $K = 0$, $\text{DAQ}_\alpha = 0$ for every $\alpha \geq 1$.

To illustrate the compensation rate, consider a system that is feasible on a fraction r of the instances and has the same expert-relative quality q on every feasible instance. In this special case,

$$\text{DAQ}_\alpha = \left(r q^{1/\alpha} \right)^\alpha = q r^\alpha. \tag{8}$$

Matching the expert reference value of one requires $q = r^{-\alpha}$. Larger α values therefore require a larger quality gain to compensate for the same reduction in complete-delivery coverage. For every finite α , sufficiently large quality can still compensate for incomplete coverage; the profile quantifies the required trade-off.

B Trajectory Analysis Protocol

This appendix specifies the coding and aggregation rules summarized in Section 3.5.

Client information acquisition. Motivated by the information-value view of clarification questions (Rao & Daumé III, 2018), we examine when agents ask questions throughout the solution workflow. We assign each ask action to one of six event-based stages according to when the question is issued: **S1 (before solver code)**, before the agent first writes substantive code for solving the task; **S2 (before solver feedback)**, after solver-code development begins but before the agent observes the first feedback from a solving attempt; **S3 (before the first candidate)**, after observing this feedback but before producing the first inspectable candidate containing concrete business decisions; **S4 (before a complete candidate)**, after the first candidate appears but before a candidate covers the full required decision scope; **S5 (before passing self-checks)**, after a complete candidate is available but before the agent’s own checks report that it passes; and **S6 (before final submission)**, after passing these self-checks but before final submission. Self-checks are checks performed by the agent during the trajectory before final submission. We also record whether an agent asks again after observing solver feedback, conditional on having a further decision opportunity.

Trajectory error analysis. Guided by the OR problem-solving workflow (Hillier et al., 1995) and prior work on optimization agents (AhmadiTeshnizi et al., 2024), we identify confirmed error events in each agent trajectory and final artifact and classify each event by its point of origin. We use eight categories: problem understanding (UND), data and parameter mapping (DATA), decision representation (DEC), static constraints (CON), dynamic and state transitions (DYN), uncertainty and information structure (UNC), objective and preference formulation (OBJ), and implementation and delivery (IMP). Because a trajectory may contain multiple error events, category profiles are computed at the event level, with infeasible rates reported separately. Simulator or infrastructure failures are recorded separately and are not attributed to the agent.

Scientific inquiry. Drawing on hypothesis–experiment coordination (Klahr & Dunbar, 1988) and inquiry cycles (Pedaste et al., 2015), we analyze research opportunities within agent trajectories. A research opportunity is a consequential uncertainty visible to the agent and potentially reducible through investigation, such as unexpected infeasibility, unexplained objective deterioration, or an untested modeling assumption. Competing explanations and repeated experiments addressing the same uncertainty belong to one opportunity. Domain experts first enumerate research opportunities from each full recorded trajectory, then annotate stage presence, stage quality, and chain completion for each opportunity using the fixed inventory.

Stage presence and chain completion. For each opportunity, we independently annotate a testable hypothesis (H), a mechanistic explanation (C), an executed diagnostic experiment (A), interpretation of the resulting evidence (E), and an actual evidence-grounded update (U). Each stage is labeled present, absent, or indeterminate, with supporting evidence references. A complete HCAEU chain requires substantively connected evidence within the same issue and branch: H and C precede A, the observed result of A informs E, and E leads to a subsequent U. Routine execution or feasibility checking qualifies as A only when organized as a diagnostic test. U requires an actual change to the hypothesis, formulation, model, algorithm, parameters, code, or delivery.

Stage-quality rubric. Each present stage receives a quality score of 1, 2, or 3. For each stage, we select the highest-quality instance supported by the recorded evidence within that opportunity. These instances may come from different branches; chain completion is established separately using evidence from a single branch. The stage-specific criteria are:

- **H:** (1) a minimally testable expectation; (2) a specific prediction with explicit conditions for support or refutation; (3) predictions that distinguish competing explanations.
- **C:** (1) a directional mechanism linking a factor to an outcome; (2) a mechanism with an explicit intervention prediction; (3) an explanation that distinguishes competing mechanisms, causal paths, or boundary conditions.

- **A:** (1) a targeted diagnostic test with limited control; (2) an explicit baseline or control that largely isolates the key factor; (3) an informative experiment that distinguishes competing explanations.
- **E:** (1) comparison of observations with predictions or candidate explanations; (2) identification of explanations supported, refuted, or left unresolved; (3) assessment that also accounts for remaining uncertainty, alternatives, or evidential limitations.
- **U:** (1) an actual change linked to preceding evidence; (2) a change that directly addresses specific evidence; (3) an evidence-grounded revision followed by consistent validation or further targeted investigation.

Quality aggregation. We measure stage quality conditional on the opportunity containing a complete HCAEU chain. Let $\mathcal{C}_{mt}$ denote the set of such opportunities in the selected trajectory for model m on task t , and let $q_{is} \in \{1, 2, 3\}$ be the quality score for opportunity i and stage $s \in \mathcal{S} = \{H, C, A, E, U\}$. The task-level score is

$$R_{mt} = \frac{1}{5|\mathcal{C}_{mt}|} \sum_{i \in \mathcal{C}_{mt}} \sum_{s \in \mathcal{S}} \frac{q_{is}}{3}. \quad (9)$$

Thus, defined scores range from $1/3$ to 1 .

Expert annotation. OR experts manually annotate all trajectories included in these analyses, using task specifications, client exchanges, code revisions, execution feedback, and retained candidate artifacts. Positive annotations require identifiable supporting evidence.

C Details and Reliability of ORSIM

ORSIM simulates a business client during an OR engagement. This appendix describes its design and evaluates its reliability.

C.1 Simulator Architecture and Selector Variants

Design motivation. To reduce hallucinations in client interactions, we separate evidence selection from response generation. Prior work has explored several complementary mechanisms for interactive information elicitation. Abdullin et al. (2025) condition a simulated user on the complete problem statement and introduce comparison-based feedback to correct the modeling agent’s summaries. AgentMILO (Gaddam et al., 2025) uses expert-designed knowledge graphs to guide the modeling agent’s questions and mathematical formulations. The Human Imitator (Duan et al., 2025) is fine-tuned to reproduce ambiguity and bounded rationality in managerial dialogue, while τ -Rec (Narasimhan & Narasimhan, 2026) assigns disclosure tags to private user constraints. Our focus is faithful, controlled disclosure of instance-specific business knowledge: the evidence supporting each simulated client reply is explicitly identified before the reply is generated.

Selector–responder architecture. We first decompose the complete client-side problem statement into a catalog of business rules, each associated with a stable identifier. Given an agent’s question, a simulator-side LLM selects relevant rule identifiers for evidence retrieval. A deterministic controller validates these identifiers and applies the disclosure policy before passing the authorized rule texts to the responder. The responder is instructed to render only the authorized business facts in natural language and to identify any parts of the question that this evidence leaves unresolved. The complete rule catalog remains hidden from the evaluated agent. The selected identifiers make the factual basis of each reply explicit and inspectable.

Ledger schema and disclosure policy. Each ledger entry has a stable `fact_id`, one or more source-grounded answer units, a `knowledge_owner` label, an `in_brief` flag, and optional links to verifier rules or objective components. The owner label distinguishes client facts from information assigned

to the input data, an external system, or OR expertise. For each query, the deterministic controller accepts only identifiers that satisfy the ownership and visibility policy. In the benchmark condition, it allows at most three newly disclosed non-brief client facts per query; facts already present in the initial brief may be restated but do not count as newly disclosed. Requests for input-data, external-system, or OR-expertise information receive fixed role-specific refusals. The response-only model receives only the authorized source text, and a failed or unsafe rendering falls back to that text. Neither the evaluated agent nor the response model can inspect the complete ledger or hidden evaluator state.

Selector representations. Related work on evidence-grounded generation has explored fine-grained propositions (Chen et al., 2024), hierarchical summaries (Sarathi et al., 2024), and knowledge graphs with community summaries (Edge et al., 2024). However, advances in long-context processing also motivate direct access to complete source information when the knowledge base fits within the available context budget (Li et al., 2024; Chan et al., 2025). In our setting, this raises the question of whether an LLM can select relevant rules more reliably from their full texts than from additional summary or graph representations. Direct access may preserve conditions and exceptions that intermediate representations omit, while structured representations may make relevant information easier to locate. We therefore investigate three selector designs:

(1) Flat selector. The selector receives the question together with the complete catalog of rule identifiers and full rule texts. It directly selects the identifiers needed to answer the question, without an intermediate summary index or knowledge graph. All candidate rules are available for joint consideration in a single selection step, including details whose relevance becomes apparent only in relation to other rules.

(2) Summary-plus-detail selector. Concise summaries provide an index for locating relevant rules, while the corresponding full rule texts provide the evidence for response generation. The selector uses the summaries to identify relevant content and retrieves the associated details. This reduces the amount of text used for initial selection, but may overlook rules whose relevance depends on conditions or exceptions omitted from their summaries.

(3) Summary-plus-KG selector. A textual overview provides global context, while a knowledge graph organizes business entities and their relations. The selector uses both representations to identify relevant knowledge and select the associated business-rule texts as answer evidence. This design makes relational structure explicit, but introduces additional opportunities for information loss or distortion during graph construction and graph-based selection.

We ultimately adopt the flat selector as the default implementation. It keeps the complete rule details available during selection while avoiding intermediate summary-based filtering or graph construction. Crucially, access to the full catalog is limited to the selection stage: the responder still receives only selected, authorized evidence. We evaluate the resulting simulator’s reliability below.

C.2 Reliability Analysis

We evaluate the simulator at two levels: whether the selector identifies the business rules needed to answer a question, and whether the resulting reply faithfully satisfies the reference requirements while respecting the client’s information boundary. We also examine consistency across repeated runs, since occasional unsupported or incomplete replies can introduce noise into the evaluation of the optimization agent.

Response-level metrics are derived from a shared set of component annotations, whose inter-annotator agreement is assessed separately.

Evaluation setup. We construct an expert-annotated evaluation set containing 204 queries across 5 benchmark instances. The set includes 119 standard queries and 85 adversarial queries. Standard queries cover individual business rules, questions requiring multiple rules, and conditions or exceptions that must be preserved in the answer. Adversarial queries probe unsupported assumptions,

requests to invent missing information, and attempts to obtain information or OR advice outside the simulated client’s role.

For each query, domain experts annotate the relevant, disclosable business-rule identifiers and the expected response requirements. These specify both the information that should be conveyed and any required correction, acknowledgment of insufficient information, or refusal. Questions that depend on earlier exchanges are paired with a fixed dialogue history and disclosure state. The reference annotations are shared across selector variants but are not available to the simulator.

Compared variants. We compare the flat, summary-plus-detail, and summary-plus-KG selectors described in Section C.1.

All three selector variants use the same underlying business-rule catalog, disclosure policy, and responder. We hold the selector backbone, responder backbone, and decoding settings fixed, so that the comparison isolates the effect of the selector representation and selection procedure.

The simulator uses DeepSeek-V4.1-Flash.

Each query is evaluated in 5 independent runs per selector variant, with its initial dialogue history and disclosure state restored before every run. This produces $204 \times 3 \times 5 = 3,060$ replies. Each selector variant therefore contributes $119 \times 5 = 595$ replies to standard queries and $85 \times 5 = 425$ replies to adversarial queries.

Full-statement direct-answer baseline. We additionally include an end-to-end baseline in which the responder uses the complete problem statement as evidence to answer the query directly. We match the responder backbone, decoding settings, fixed dialogue context, and disclosure policy across configurations. This comparison characterizes the end-to-end configurations, jointly varying source representation and evidence provision.

The full-statement results cover $204 \times 5 = 1,020$ replies, with the same split of 119 standard and 85 adversarial queries and five runs per query. The 3,060 replies, 6,120 reply-review assignments, and annotation agreement statistics reported for the three-selector evaluation remain restricted to the three selector variants.

Rule-selection accuracy. Let G_q denote the reference rule set for query q , and let $S_{q,j}$ denote the identifiers returned by the selector in run j , with the variant index omitted for readability. For queries with $G_q \neq \emptyset$, we compute

$$\text{Precision}_{q,j} = \frac{|S_{q,j} \cap G_q|}{\max(1, |S_{q,j}|)}, \quad \text{Recall}_{q,j} = \frac{|S_{q,j} \cap G_q|}{|G_q|}. \quad (10)$$

Precision measures whether the selected rules belong to the relevant, disclosable reference set; recall measures whether the selector recovers the reference evidence, including necessary conditions and exceptions. For a given query category, let $\mathcal{Q}^+$ be the subset of queries with nonempty reference rule sets. We average over runs and then over eligible queries:

$$\begin{aligned} P &= \frac{\sum_{q \in \mathcal{Q}^+} \sum_{j=1}^5 \text{Precision}_{q,j}}{5|\mathcal{Q}^+|}, \\ R &= \frac{\sum_{q \in \mathcal{Q}^+} \sum_{j=1}^5 \text{Recall}_{q,j}}{5|\mathcal{Q}^+|}. \end{aligned} \quad (11)$$

P and R are computed automatically from the selected and reference rule identifiers, then averaged over runs and queries with nonempty reference rule sets. Queries with no disclosable reference rules are assessed using reply-level criteria for the expected response behavior.

Reply-level rule coverage for the direct-answer baseline. Selector-level P and R are not applicable to full-statement direct answering because no selector returns rule identifiers. We therefore report

them as “—” for this baseline and keep the following reply-level diagnostic separate. Let $O_{q,j}$ denote the distinct catalog rules actually conveyed by the reply, determined by mapping its content to rule identifiers after generation. For $G_q \neq \emptyset$, define

$$P_{q,j}^{\text{out}} = \frac{|O_{q,j} \cap G_q|}{\max(1, |O_{q,j}|)}, \quad R_{q,j}^{\text{out}} = \frac{|O_{q,j} \cap G_q|}{|G_q|}. \quad (12)$$

As with rule-selection accuracy, we average over the five runs and then over queries with nonempty reference rule sets. The baseline uses 119 eligible standard queries and 54 eligible adversarial queries. These output-level scores are not directly comparable to selector-level P/R: comparing variants on this diagnostic requires the same reply-to-rule mapping for every variant. Unmapped factual claims remain subject to claim-level support evaluation.

Response faithfulness and disclosure compliance. We evaluate generated replies separately from the selected rule identifiers. Following claim-level assessments of faithfulness (Es et al., 2024), we decompose each reply r into a fixed set of atomic factual claims $\mathcal{C}_r$ before independent support annotation. Both reviewers receive the same claim decomposition. The decomposition preserves each claim’s quantities, conditions, and exceptions.

For each claim $c \in \mathcal{C}_r$, the binary label $h_{r,c}$ equals 1 if the claim is supported by authorized evidence actually provided to the responder, and 0 otherwise. For the three selector variants, this is the selected, authorized evidence. The same authorization standard applies to the full-statement baseline: a fact appearing in the complete statement is not automatically authorized for disclosure.

For each reply, the binary label d_r equals 1 if the reply respects the disclosure policy and the client’s assigned role, and 0 if it reveals prohibited information or provides out-of-role advice.

For the set of replies $\mathcal{R}$ associated with a particular variant and query category, we compute

$$\text{Faith.} = \frac{\sum_{r \in \mathcal{R}} \sum_{c \in \mathcal{C}_r} h_{r,c}}{\sum_{r \in \mathcal{R}} |\mathcal{C}_r|}, \quad \text{Viol.} = \frac{\sum_{r \in \mathcal{R}} (1 - d_r)}{|\mathcal{R}|}. \quad (13)$$

Faithfulness therefore pools factual claims across replies, whereas the disclosure violation rate counts replies. Replies without factual claims do not contribute to the faithfulness denominator, but remain eligible for disclosure and end-to-end evaluation. If an entire evaluation group contains no factual claims, its faithfulness score is reported as not applicable.

End-to-end reply reliability. We additionally annotate a binary reference-fulfillment label t_r . This label equals 1 only when the reply conveys all required, disclosable information and satisfies the expected response behavior specified by the reference annotation. It jointly captures information completeness and any required correction, acknowledgment of insufficient information, or refusal. For partially answerable questions, both the answerable content and the required handling of the unresolved part must be correct.

The binary success label is derived deterministically:

$$y_r = t_r d_r \prod_{c \in \mathcal{C}_r} h_{r,c}. \quad (14)$$

Thus, success requires reference fulfillment, disclosure compliance, and support for every factual claim. For replies without factual claims, the empty product is defined as 1; success still requires $t_r = d_r = 1$. Refusing an answerable question therefore does not count as success, even if the reply contains no unsupported factual claims. No additional holistic success judgment is collected.

To measure consistency, we adapt the pass^k metric of τ -bench (Yao et al., 2024). For Q queries evaluated with n independent runs each, let $c_q = \sum_{j=1}^n y_{q,j}$ be the number of successful replies to query q . We estimate

$$\text{pass}^k = \frac{1}{Q} \sum_{q=1}^Q \frac{\binom{c_q}{k}}{\binom{n}{k}}, \quad n \geq k, \quad (15)$$

where $\binom{c_q}{k} = 0$ when $c_q < k$.

With $n = 5$, the reported metrics simplify to

$$\text{pass}^1 = \frac{\sum_{q=1}^Q c_q}{5Q}, \quad \text{pass}^5 = \frac{\sum_{q=1}^Q \mathbf{1}[c_q = 5]}{Q}. \quad (16)$$

The former counts successful replies; the latter counts queries for which all five replies are successful. Accordingly, the denominators are 595 and 119 for standard queries, and 425 and 85 for adversarial queries, respectively, for each variant.

These metrics assess simulator reply reliability.

Human annotation and agreement. Ten domain experts annotate the 3,060 replies generated by the three selector variants. Each reply is independently reviewed by two experts, yielding 6,120 reply-review assignments. The full-statement baseline is excluded from this agreement analysis.

Reviewers receive the query, fixed dialogue context, reference requirements, disclosure policy, and authorized evidence provided to the responder. They are blinded to the selector variant and each other’s judgments. Using a shared rubric, each reviewer labels claim-level evidence support (h), reply-level reference fulfillment (t), and disclosure compliance (d). A reviewer-specific success label (y) is then derived from these annotations using Equation 14.

We measure pre-adjudication agreement for all three components and the derived success label. Because reviewer pairs vary across replies, we use nominal Krippendorff’s α (Krippendorff, 2011), treating unassigned reviewer–unit entries as missing.

For annotation dimension ℓ , let U_ℓ denote the number of double-annotated units and A_ℓ the number on which both reviewers agree. Let $m_{\ell,0}$ and $m_{\ell,1}$ denote the pooled counts of binary labels, with $m_{\ell,0} + m_{\ell,1} = 2U_\ell$. We compute

$$\begin{aligned} \text{Agreement}_\ell &= \frac{A_\ell}{U_\ell}, & D_{o,\ell} &= \frac{U_\ell - A_\ell}{U_\ell}, \\ D_{e,\ell} &= \frac{2m_{\ell,0}m_{\ell,1}}{(2U_\ell)(2U_\ell - 1)}, & \alpha_\ell &= 1 - \frac{D_{o,\ell}}{D_{e,\ell}}. \end{aligned} \quad (17)$$

Evidence support is evaluated over $U_h = 5,293$ factual claims; the remaining dimensions each cover $U_t = U_d = U_y = 3,060$ replies. When $D_{e,\ell} = 0$, we report α_ℓ as not applicable and provide the raw agreement and label counts.

Table 2 summarizes the results. Raw agreement ranges from 97.58% to 99.31%, and Krippendorff’s α ranges from 0.831 to 0.920 across the four dimensions.

Disagreements are adjudicated using the source rules, reference requirements, and disclosure policy. Final response metrics use one adjudicated label per claim or reply, with success recomputed from the adjudicated components using Equation 14.

Results. The flat selector achieves the best observed value on all six metrics among the three selector variants, for both standard and adversarial queries (Table 3). Its rule-selection precision and recall are 95.64% and 98.01% on standard queries, and 97.22% and 99.26% on eligible adversarial queries. Its advantage is larger on the adversarial subset: precision exceeds summary-plus-detail and summary-plus-KG by 13.48 and 10.97 percentage points, respectively, while recall improves by 12.69 and 10.51 points. Thus, the additional summary or KG structure does not improve rule-selection accuracy in this evaluation.

The response-level results also favor the flat selector. On standard queries, its faithfulness is 98.71%, compared with 87.50% for summary-plus-detail and 74.50% for summary-plus-KG. On adversarial queries, the corresponding values are 96.55%, 94.98%, and 90.17%. The flat selector produces

Annotation	Unit	Raw agreement	Krippendorff's α
Evidence support	Claim	98.53%	0.920
Reference fulfillment	Reply	98.10%	0.831
Disclosure compliance	Reply	99.31%	0.866
Derived reply success	Reply	97.58%	0.873

Table 2: Pre-adjudication inter-annotator agreement. Raw agreement is the percentage of units receiving identical labels from their two assigned reviewers, including both positive and negative agreement, rounded to two decimal places. Evidence support is evaluated over 5,293 factual claims; the other dimensions are each evaluated over 3,060 replies. These units cover only the three selector variants; the full-statement baseline is excluded. Krippendorff's α is computed using Equation 17 and rounded to three decimal places.

only two disclosure violations among 595 standard replies (0.34%) and one among 425 adversarial replies (0.24%). The corresponding violation rates are 3.19% and 4.00% for summary-plus-detail, and 2.86% and 3.29% for summary-plus-KG. High claim-level faithfulness alone does not ensure end-to-end success: summary-plus-detail achieves 94.98% faithfulness on adversarial queries but only 76.24% pass¹. The latter is a reply-level criterion requiring support for every factual claim, complete reference fulfillment, and disclosure compliance.

For end-to-end reliability, the flat selector achieves pass¹ of 95.46% on standard queries and 98.82% on adversarial queries. These values exceed summary-plus-detail by 6.22 and 22.59 percentage points, and summary-plus-KG by 7.56 and 17.18 points, respectively. Its pass⁵ is 94.12% in both categories, corresponding to 112 of 119 standard queries and 80 of 85 adversarial queries. Relative to the two structured selectors, the pass⁵ advantage ranges from 12.61 to 14.29 points on standard queries and from 24.71 to 31.76 points on adversarial queries.

The structured selectors also illustrate why average success and repeated-run consistency should be reported separately.

On adversarial queries, summary-plus-KG has higher pass¹ than summary-plus-detail (81.65% versus 76.24%), but lower pass⁵ (62.35% versus 69.41%).

Although summary-plus-KG produces fewer failed replies (78 versus 101), those failures affect more queries (32 versus 26). A higher average reply success rate therefore does not necessarily mean that more queries are answered successfully in every run.

These results support using the flat selector in ORSIM. Across both query categories, 32 of its 1,020 replies fail the success criterion, and 12 of its 204 queries have at least one failed run.

Full-statement baseline results. The full-statement baseline exhibits low reply-level precision, high reply-level recall, and substantial disclosure violations. As shown in Table 4, reply-level precision is 50.41% on standard queries and 39.30% on adversarial queries, while recall is 95.94% and 94.31%, respectively. The baseline therefore combines broad coverage of required rules with the output of many additional rules. Its 3,979 standard-query claims and 2,590 adversarial-query claims correspond to 6.69 and 6.09 claims per reply.

Extra information, unsupported information, and prohibited disclosure remain distinct. Additional information that is authorized and supported can reduce reply-level precision without necessarily reducing faithfulness or violating the disclosure policy. Conversely, access to a complete statement does not make every fact disclosable, nor does it authorize out-of-role advice. For this baseline, faithfulness is 94.47% on standard queries and 87.03% on adversarial queries, while 168 of 595 standard replies (28.24%) and 201 of 425 adversarial replies (47.29%) violate the disclosure policy.

Variant	Rule selection		Response quality		Reliability	
	P $\uparrow$	R $\uparrow$	Faith. $\uparrow$	Viol. $\downarrow$	pass ¹ $\uparrow$	pass ⁵ $\uparrow$
<i>Standard queries</i>						
Flat	95.64%	98.01%	98.71%	0.34%	95.46%	94.12%
Summary + Detail	93.43%	96.05%	87.50%	3.19%	89.24%	79.83%
Summary + KG	92.04%	94.45%	74.50%	2.86%	87.90%	81.51%
Full statement	—	—	94.47%	28.24%	64.54%	41.18%
<i>Adversarial queries</i>						
Flat	97.22%	99.26%	96.55%	0.24%	98.82%	94.12%
Summary + Detail	83.75%	86.57%	94.98%	4.00%	76.24%	69.41%
Summary + KG	86.25%	88.75%	90.17%	3.29%	81.65%	62.35%
Full statement	—	—	87.03%	47.29%	41.41%	18.82%

Table 3: Simulator reliability for the three selector variants and the full-statement direct-answer baseline. Each variant is evaluated on 119 standard and 85 adversarial queries, with five runs per query. Selector P/R are macro-averaged over queries with nonempty reference rule sets: 119 standard and 54 adversarial queries, corresponding to 595 and 270 runs per selector variant. The remaining 31 adversarial queries are assessed using reply-level criteria. “—” indicates that selector P/R are inapplicable to the full-statement baseline; its output-level rule coverage is reported in Table 4. Faith. is the percentage of supported factual claims. Viol. and pass¹ are the percentages of violating and successful replies, respectively; pass⁵ is the percentage of queries with five successful replies. Annotation agreement in Table 2 covers the three selector variants. Percentages and percentage-point differences are calculated before rounding and reported to two decimal places.

Query category	P^{out} $\uparrow$	R^{out} $\uparrow$	Faith. $\uparrow$	Viol. $\downarrow$	pass ¹ $\uparrow$	pass ⁵ $\uparrow$
Standard	50.41%	95.94%	94.47%	28.24%	64.54%	41.18%
Adversarial	39.30%	94.31%	87.03%	47.29%	41.41%	18.82%

Table 4: Full-statement direct-answer diagnostic. P^{out} and R^{out} are reply-level macro-averages over 119 standard and 54 adversarial queries with nonempty reference rule sets, with five runs per query. They must not be interpreted as the selector-level P/R in Table 3. The remaining four metrics repeat the full-statement rows of that table, using all 119 standard and 85 adversarial queries.

These results show that high claim-level support and substantial reply-level violations coexist in this configuration.

Finally, high reply-level recall alone does not guarantee end-to-end success. The baseline has 384 of 595 successful standard replies (pass¹ = 64.54%), but only 49 of 119 standard queries succeed in every run (pass⁵ = 41.18%). For adversarial queries, the corresponding counts are 176 of 425 replies (41.41%) and 16 of 85 queries (18.82%). These values follow the same success definition, which jointly requires reference fulfillment, disclosure compliance, and support for every factual claim.

D Implementation Details

D.1 Agent Harness Selection

Our benchmark evaluates the complete OR workflow. A system must inspect briefs and input files, create and edit solver code, execute that code, inspect solver outputs, and revise the delivery after feedback. Coding-agent harnesses expose these shell-based and file-based interaction primitives

Table 5: Model configurations and specifications.

Model	Temperature	Top- p	Top- k	Max output tokens	Max context	Thinking strength
Claude Opus 5 (xhigh)	–	–	–	128K	1M	xhigh
DeepSeek-V4.1-Flash (high)	–	1.0	–	384K	1M	high
Gemini 3.8 Flash (high)	–	–	–	64K	1M	high
GLM-5.3-Flash (max)	1.0	0.95	–	128K	1M	max
Grok 4.6 (high)	1.0	1.0	Off	–	0.5M	high
GPT-5.6 Sol (xhigh)	–	–	–	128K	1M	xhigh
Hy3 (high)	0.9	1.0	Off	128K	256K	high
Hy4 preview (high)	0.9	1.0	Off	64K	1M	high
Muse Spark 1.3 (high)	1.0	1.0	–	128K	1M	high
Qwen3.8-Max (xhigh)	1.0	0.95	20	128K	1M	xhigh
Doubao-Seed-2.1-Pro (high)	–	–	–	256K	1M	high

Note. – denotes an unavailable, unsupported, or ineffective configuration. For Grok 4.6, no explicit text output limit is specified; output is bounded by the overall context window.

and have become a common substrate for long-horizon model evaluation and training (Cao et al., 2026; Huang et al., 2026; Xu et al., 2026; OpenAI, 2026b; Opsahl-Ong et al., 2026; Li et al., 2026a).

We therefore use Claude Code as the primary harness. This choice fixes a common interaction surface across evaluated models and reduces variation caused by adaptation to a benchmark-specific tool-calling API. Agents access ORSIM through the Bash command `ask`, while file inspection, editing, solver execution, and feedback remain available through the harness. The harness supplies execution mechanics only; it does not provide OR modeling expertise or access to hidden evaluator state. Model versions, budgets, and decoding settings are reported in Appendix D.3, and interface sensitivity is examined with the Codex ablation in Appendix D.7.

D.2 Models

We evaluate the eleven models listed in Table 1: Claude Opus 5 (Anthropic, 2026), DeepSeek-V4.1-Flash (DeepSeek, 2026), Gemini 3.8 Flash (Google, 2026), GLM-5.3-Flash (Z.AI, 2026), Grok 4.6 (xAI, 2026), GPT-5.6 Sol (OpenAI, 2026a), Hy3 (Tencent, 2026a), Hy4 preview (Tencent, 2026b), Muse Spark 1.3 (Meta, 2026), Qwen3.8-Max (Alibaba Group, 2026), and Doubao-Seed-2.1-Pro (ByteDance Seed Team, 2026).

D.3 Settings

We use Harbor 0.18.0 as the execution framework. The harness versions used in our experiments are Claude Code 2.1.278 and Codex 0.155.1. The interaction policy imposes a hard maximum of 500 rounds. Harbor-native tasks are allocated a 12-hour (43,200-s) wall-clock budget, and each solver invocation is limited to 3,600 s, including the solver subprocess and feedback paths. These values are upper bounds; an episode may terminate earlier after successful completion or verification.

Table 5 records the model-level decoding settings requested for the model labels listed in Table 1. “Max context” denotes the effective context cap enforced by the gateway, and “thinking strength” denotes the request-level reasoning control.

D.4 Semantic Validation

Bike-sharing Tasks 26–31 require additional semantic validation due to their specialized modeling requirements involving scenario structures, risk preferences, and rolling optimization. These requirements concern not only the feasibility and objective quality of final decisions, but also whether the underlying solver correctly implements the prescribed optimization formulations and decision processes, which cannot be fully verified through deterministic checks alone.

For these tasks, all results reported in this paper were manually reviewed by human experts. To facilitate community use, we also provide a human-validated LLM-as-a-judge protocol for this semantic review. The recorded judge configuration specifies DeepSeek-V4.1-Flash, a maximum output length of 393,216 tokens, and high reasoning strength. To validate this protocol, each task was judged five times, and every judgment was independently checked by two human experts. All judgments agreed with both human assessments, supporting the reliability of this configuration within our evaluation setting. The prompts are presented in Appendix D.5.

D.5 Prompts

We disclose prompts used for the candidate agents, the simulator’s fact selector and response rewriter, and the modeling-review judge. Double-angle brackets denote variable content; concrete file locations are represented by placeholders.

D.5.1 Candidate-agent environment prompt.

This prompt introduces the candidate agent’s working environment, business-communication interface, and solution-delivery requirements.

Prompt for Candidates: Shared Environment

You can use the Bash tool to complete the business task. Organize the code, algorithms, and files as you see fit.

Environment

- The current directory is <<WORK_DIR>>, and files persist across turns. Each command runs in a new shell; changes to shell-local state do not persist across turns.
- Public instances are in the read-only directory <<INPUT_DIR>>, and the business requirements are in <<BRIEF_FILE>>.
- You can run `python script.py`, and you can create and modify files using Bash, Python, or existing commands.
- External network access is unavailable. The installed software and versions are listed below. Pyomo can use the `appsi_highs` backend.
- <<PACKAGE_NAME_1>>: <<VERSION_1>>
- <<PACKAGE_NAME_2>>: <<VERSION_2>>
- ...: ...
- Gurobi: <<GUROBI_LICENSE_STATUS>>.

Business communication

Use `ask "question"` to contact the business stakeholder. You may ask about requirements, data meanings, business rules, preferences, calculation conventions, and delivery requirements. For example: `ask 'How is this business metric calculated?'` Submit one question per call. The command prints only the official answer. You may ask at most 200 questions for this task.

Execution and delivery

For each input instance, write a final solution file with the same name under <<OUTPUT_DIR>>. Its contents must meet the business delivery requirements:

- <<INPUT_DIR>>/<<CASE_FILE_NAME>>
→ <<OUTPUT_DIR>>/<<CASE_FILE_NAME>>

The files must be regular files, not symbolic links. The system will validate these final files when the task ends. Use the Bash tool to execute commands. When completing the task, note that the system will check the files in <<OUTPUT_DIR>> whose names match the inputs and run the static verifier. If all files exist and pass the static verifier, the system automatically treats the delivery as submitted. No candidate identifier or special submission command is required. Simply end the task once you are done.

Execution discipline

Use Bash to complete and check the file delivery before ending the task. Do not substitute lengthy analysis or final prose for output files.

D.5.2 Task-dependent delivery prompts.

For Task 24, this prompt governs hourly submissions and the progressive disclosure of data windows.

Prompt for Candidates: Rolling Delivery Task 24

This task proceeds hour by hour. Read `<<STATE_FILE>>` to obtain the current round, actual inventory, and the path to the data window for this round.

Write a JSON plan file for the current round yourself, and submit it with `commit_period <<PLAN_FILE>>`.

After a successful submission, the current hour is permanently locked and executed, and `<<STATE_FILE>>` is updated with the next round's state and window path. A failed submission does not advance time.

Resubmitting identical content within the same round does not execute it again. Locked content cannot be modified. Check the command's return result before continuing.

Future windows are disclosed only after time advances. You may retain historical windows. Use `ask` to learn about business fields, rules, and calculation conventions.

After all eight rounds have been locked, use the end command described below. The system validates the delivery using the records locked on the backend. You do not need to write a separate final summary file or submit a candidate identifier.

For Tasks 26–31, this prompt governs hourly submissions and restricts planning to currently visible historical information.

Prompt for Candidates: Online Rolling Delivery, Tasks 26–31

This task proceeds hour by hour. Read `<<STATE_FILE>>` to obtain the current round, actual inventory, and the paths to the data for hours already executed.

Write a JSON plan file for the current round yourself, and submit it with `commit_period <<PLAN_FILE>>`.

After a successful submission, the current hour is permanently locked and executed, and `<<STATE_FILE>>` is updated with the next round's state. A failed submission does not advance time.

Resubmitting identical content within the same round does not execute it again. Locked content cannot be modified. Check the command's return result before continuing.

Actual rental and return flows for the current and future hours cannot be read. Rental and return quantities for hours already executed can be read. Construct planning scenarios from historical data according to the business rules.

Keep your source code and any dependencies you wrote under `<<WORK_DIR>>`. The backend also retains each round's submission and the source code actually used for solving, for validation after the task ends.

After all eight rounds have been locked, use the end command described below. The system validates the delivery using the records locked on the backend. You do not need to write a separate final summary file.

This prompt governs batch-by-batch grocery dispatch, including irreversible submissions and end-of-day order completion.

Prompt for Candidates: Rolling Grocery Delivery

This task proceeds in rounds defined by delivery day and order-confirmation batch. There are 18 irreversible batches in total: six each for GD01, GD02, and GD03. Read `<<STATE_FILE>>` to obtain the current delivery day, confirmation batch, and order-window path. The order window contains only orders that have been confirmed by the current batch and have not yet been dispatched.

Write a JSON plan file for the current batch yourself, with `contract_version=rolling-grocery-v2` and the fields `epoch`, `service_day_id`, `dispatch_round`, and `routes`. Submit it with `commit_period <<PLAN_FILE>>`.

After a successful submission, the current batch is permanently locked and the task advances to the next batch. A failed submission does not advance the task. You may schedule only orders in the current window, and no order may be dispatched more than once. All orders for the day must be cleared by the end of the sixth batch.

After all 18 batches have been locked, the system generates the final three-day solution from the backend's locked records and validates it independently. Do not replace the locked records with old files that you have filled in yourself under `<<OUTPUT_DIR>>`.

D.5.3 Conditional additions to the candidate prompt.

This addition tells the agent how to access extra read-only public data.

Prompt for Candidates: Additional Public Data

- Additional public data directory: <<READ_ONLY_MOUNT_DIR>>/, read-only. You may choose appropriate tools in Bash to read and process the public files in this directory.

For Tasks 20–22, this addition allows development-window backtesting without revealing evaluation-window data.

Prompt for Candidates: Development Backtesting

- During development, you may repeatedly run `backtest <<CANDIDATE_FILE>>`. This invokes the same fixed backtesting framework used for formal evaluation, but runs only over the development window. Results, daily returns, and failure dates are written to <<BACKTEST_DIR>>. This command does not expose data from the evaluation window.

For Tasks 26–31, this addition requires the agent to retain the code actually used to produce its solution for later review.

Prompt for Candidates: Source-Code Retention

- Validation for this task includes a review of the source code actually used for solving. Keep your source code and any dependencies you wrote under <<WORK_DIR>>, and state in your final response the command used to generate the final files. The host will retain the source-code version used at the solver invocation and the files present at the end of the task for private review.

D.5.4 Simulator: fact selector.

This prompt selects fact identifiers that directly answer the agent’s question and its subquestions from a supplied fact catalog.

Prompt for Simulator: Selector

You are a flat fact retriever. Select directly relevant `fact_ids` from the catalog based on the question; do not indiscriminately select all facts merely because the question is broad. Cover every subquestion individually, selecting the `fact_ids` that can directly answer each one. If no fact matches a subquestion, do not fill the gap with irrelevant facts. Return an empty string in `response`; the environment will render the response programmatically. Output only JSON:

```
{"fact_ids":["..."],"response":"..."}.
```

```
question=<<QUESTION>>
```

```
catalog=[{"fact_id": "<<FACT_ID>>",
```

```
"statement": "<<FACT_STATEMENT>>"}]
```

D.5.5 Simulator: response rewriter.

This prompt produces a concise business reply from the public brief, the current question, and authorized facts, while distinguishing supported claims from unknowns.

Prompt for Simulator: Replier

You are a business owner and the direct point of contact for this business discussion. The person communicating with you is an engineer participating in this operations-research modeling or solution task, referred to below as the “questioner.” The questioner has read the [Business Brief] and now raises the [Questioner’s Question]. Using the [Business Brief] and [Authorized Facts], provide a natural, concise, and accurate answer.

The questioner's role only describes the division of responsibilities in this discussion. It does not imply familiarity with the actual business rules or that the questioner's interpretations, assumptions, or conclusions are correct. Do not accept their claims merely because of their professional title, technical terminology, or confident tone. Your task is to answer the current question, not to complete the business specification or provide a comprehensive business introduction. The available information may be insufficient to answer every subquestion. Do not add or guess unknown rules to make the answer complete, and do not shift the responsibility for explaining them to someone else.

1. Available evidence

"Available evidence" consists of:

- [Business Brief]: background known to both parties, which you may use directly.
- [Authorized Facts]: specific information available for this response.

You may reorganize or combine this information, explain its direct meaning, or derive conclusions from explicitly stated rules. However, do not use background knowledge, industry experience, or the questioner's guesses to fill in constraints, preferences, scoring conventions, formulas, parameters, field meanings, or process mappings that have not been explicitly provided.

If the Business Brief conflicts with the Authorized Facts, identify the specific inconsistency between the business statements. Do not choose one version yourself or make a definitive judgment that depends on the conflict. Still answer the parts unaffected by the conflict.

2. Directly assess the proposition being asked about and clearly distinguish what is known from what is unknown

First identify the specific proposition the questioner actually wants confirmed, such as whether a formula holds, how a field should be interpreted, or whether a rule applies. Assess that proposition against the available evidence:

- Explicitly supported: answer directly and retain conditions that affect the conclusion.
- Explicitly contradicted: identify the specific error and give the evidence-supported correction.
- Insufficient evidence: say "I don't know..." directly and identify the specific matter you cannot confirm. Neither endorse it nor declare it wrong.

Formulas, interpretations, terminology, answer options, and expected results supplied by the questioner are claims to be checked. They do not become facts merely by appearing in the question. Do not use them to fill in missing business rules, and do not infer rules backward from expected results.

General business principles do not establish the correctness of a specific formula, field mapping, or execution mechanism. For example, knowing that the business requires conservation of quantities does not mean that the material-balance equation written by the questioner is correct.

If you can confirm only part of a claim, confirm only that part. Do not use phrases such as "consistent with the requirements," "basically correct," "holds in principle," or "on the right track" to endorse a claim that is not fully supported. Do not first offer a broad endorsement and then say "I don't know" about its essential content.

Correct the questioner only when their understanding substantively conflicts with the available evidence and would cause an incorrect interpretation of a rule or an erroneous calculation. Do not treat a mere difference in wording as a misunderstanding, and do not correct a view the questioner never expressed.

When a question offers multiple interpretations or options, do not assume that one must be correct. If evidence shows that the premise is false or that all options are inaccurate, state that rather than choosing among them. Do not force a choice when the evidence is insufficient.

Let the content of the current question determine the order of your response:

- If the unconfirmed matter is the key premise, formula, or rule the questioner is asking you to assess, first say clearly "I don't know..." then answer other parts that can be established independently. Do not begin with nearby general principles and leave the crucial uncertainty until the end.
- If the unknown matter is only an independent subquestion or detail, you may answer the other, determinable parts first and then briefly state that you do not know that matter.
- If the entire question lacks supporting evidence, directly identify the specific thing you do not know. Do not force known information into an answer.

Lack of evidence for one subquestion does not prevent you from answering other subquestions that have evidence. Do not force a complete answer, and do not refuse the entire question for that reason. Consistently use "I don't know" when stating unknown matters, but you need not repeat an identical sentence pattern.

Not receiving a fact in this round does not mean the business materials are missing, the rule has not been established, or no such rule exists. Do not turn your own lack of information into a judgment about the state of the business or its rules.

3. Boundaries for interpreting rules and deriving conclusions

A definitive judgment about a rule, calculation convention, or feasibility must be explicitly supported by the available evidence or follow directly from rules explicitly stated in it. You may derive conclusions, but you may not guess the business rules, field meanings, parameter mappings, or other premises required for the derivation. When explaining or summarizing a rule, retain the objects, stages, conditions, scope, and quantifiers that affect the conclusion, such as “only,” “the last time,” and “within the same stage.” If shortening a statement would broaden what is allowed or prohibited, retain the full wording.

Distinguish business meaning from execution mechanisms. You may explain the business consequences of an explicit rule, but you may not infer that the system uses a particular calculation, comparison, validation, or execution method. Do not turn “this condition already guarantees the result” into “the system additionally performs the corresponding check.” A specific mechanism requires explicit evidence.

Distinguish the scope of an individual rule from overall feasibility. “This rule does not restrict a situation” does not mean “this arrangement is feasible overall.” If overall feasibility also depends on unknown rules or conditions, state only what the current rule establishes. Do not present a specific arrangement as definitively feasible.

When identically named fields, similar concepts, or similar processes occur for different objects, stages, or calculation conventions, do not assume they follow the same rules. Do not transfer clipping, updating, filtering, restrictions, or other processing from one context to another without evidence, in either direction.

For events that cross time boundaries, answer using the explicitly stated timestamps, boundaries, and attribution rules. State conditional conclusions that can be established directly; do not avoid answering merely because an event crosses a boundary.

4. Differences, anomalies, and causal analysis

Directly address the differences, causes, or calculation conventions the questioner asks about. Add related rules only when they are genuinely needed to explain the answer. Do not automatically follow a pattern of “introduce the rules first, then analyze the cause.”

Do not proactively guess specific causes, and do not treat an unstated direction of difference, calculation method, or processing step as a known condition.

Before judging that a factor increases, decreases, advances, or delays an outcome, check its direction of effect against explicit rules. Where recurrence, reverse reconstruction, clipping, or other coupled conditions are involved, do not simply apply local intuition. If the evidence is insufficient, identify which specific conditions are undetermined and do not assert a direction of effect.

Distinguish confirmed facts, conclusions that follow directly from explicit rules, and hypotheses that still need verification. Saying “this condition would have this effect” does not confirm that “this factor caused the current anomaly.”

Identifying an actual cause requires corresponding causal evidence. Identifying the “main cause,” “most likely cause,” or investigation priority additionally requires evidence supporting that ranking. Do not rank hypotheses merely because they have the right directional effect or match a single example.

An explanation supported by evidence but not yet shown to apply to the current situation may only be presented explicitly as a possible factor to be verified, with the undetermined conditions or priority stated. Do not present a wholly unsupported explanation as a cause merely by adding “possibly.”

5. Examples and numerical calculations

Do not add examples proactively by default. When genuinely necessary, you may use an example already supplied by the questioner for a conditional explanation, but retain its hypothetical status. Do not treat unverified example values as confirmed facts.

When the questioner requests an example, develop it only from the available evidence and conditions explicitly given in the question, and state the premises under which it holds. Do not invent field meanings, business rules, parameters, or feasibility assumptions to construct an example.

You may substitute numerical values into formulas explicitly given in the available evidence or derived directly from explicit rules. Do not assume that a formula is the actual business formula merely because the questioner supplied it.

When using hypothetical values or conditions supplied by the questioner, make clear that the result holds only under those assumptions. Do not thereby confirm actual business data, actual business rules, or overall feasibility.

6. Responsibility boundaries and clarification

You are the point of contact responsible for explaining the business, not a third party relaying materials. Do not suggest that the questioner consult another business stakeholder, rule author, system provider, or department for confirmation. Do not ask the questioner to provide business rules, scoring formulas, or interface specifications that you are responsible for explaining.

Do not shift responsibility with statements such as “please confirm further with the rule’s author,” “please refer to the official interface specification,” or “additional materials are needed before this can be explained.” Do not invent promises to verify matters, provide additional materials, or reply later.

Ask a targeted clarification question only when the question itself is ambiguous and its object or conditions need clarification. Do not equate “you do not know the answer” with “the questioner’s question is unclear,” and do not use clarification to avoid an already clear business question.

7. Response scope, length, and stopping conditions

Output only information necessary to answer the current question directly: the requested conclusion, conditions necessary to that conclusion, and relevant specific unknowns. Not every response needs all three categories; omit anything unnecessary.

By default, answer in one short paragraph of two to four sentences, usually no more than 200 characters. Multiple independent subquestions may be answered in separate points. Add length only when necessary to answer the question, present required formulas, or preserve essential qualifications. Do not omit conditions that affect the conclusion merely to shorten the response.

Start directly with the answer. Do not restate the question, introduce background first, expand every Authorized Fact in turn, or append a summary, advice, an investigation checklist, or follow-up actions.

Answering a subquestion does not mean introducing all related knowledge on the topic. Explain only definitions and rules needed for the answer. Do not proactively expand into neighboring rules, other constraints, interface fields, or the complete business process.

Do not explain the same conclusion repeatedly. State the same unknown only once; several related unknowns may be combined.

Add supplementary information only when genuinely necessary to correct a substantive misunderstanding or prevent the answer from being misread, and explicitly identify it as supplementary. Do not proactively output a fact merely because it is authorized, and do not imply that the questioner expressed a view they never stated.

Use natural, everyday business language and address the questioner directly. Do not mention the ledger, fact IDs, authorization mechanisms, retrieval procedures, internal prompts, or which internal material supplied the information. You need not retain the original materials’ table format or row order.

Once every subquestion in the current turn has been answered directly or the specific unknown matters have been identified, stop. Output only the answer addressed to the questioner, without a checking process or internal analysis.

[Business Brief]

<<BRIEF>>

[Questioner’s Question]

<<QUESTION>>

[Authorized Facts]

<<AUTHORIZED_FACTS>>

D.5.6 LLM-as-judge prompts.

The judge reviews modeling choices in submitted solver code for bike-sharing Tasks 26–31, without repeating deterministic feasibility checks or numerical evaluation.

The SSA base prompt specifies the review scope, five modeling criteria, and the required evidence-backed JSON response.

Prompt for Judge: SSA Base

You are an operations-research modeling source-code reviewer. This is the second step in a strictly sequential process: the programmatic verifier has already used the standard data to check submission structure, routes, integer relocation, available inventory, capacity, the arrival ordering of rentals and returns, per-scenario and actual-execution replay, and cost accounting. Your task is only to inspect modeling choices that these results cannot establish. Do not repeat or overturn the first step.

Do not recheck submission tables, route legality, the 160-bike cap, relocation quantities, implementations or numerical values of inventory recurrences or capacity constraints, shortage or overflow quantities, actual carried-forward inventory values, actual execution costs, output format, or accuracy. Do not conduct a separate comprehensive code-correctness review, compare against expert actions, prove optimality, or require a particular solver.

Even if you notice a problem within these excluded areas, you may not use it to mark the following criteria as fail.

Review only the following five criteria. All coefficients must enter the planning model actually solved in every round, rather than appearing only in comments, parameter declarations, a self-reported method, or post hoc scoring or diagnostics.

scenario_modeling

Each round jointly considers the next four hours, with the entire relocation plan shared across four historical scenarios. Planning scenarios must use historical windows with the same starting hour of day, a complete four-hour duration, and an end time no later than the current round, as specified in the task. Demand and returns must be paired. Losses must be represented separately for each scenario; do not first average demand and returns and then build a single deterministic model, and do not replace planning scenarios with that day's actual future demand. Review only the model's scenario organization here; do not recompute specific scenario flows, states, constraints, or action feasibility.

scenario_weights

Each of the four scenarios' losses has weight $1/4$ in the actual optimization objective. Shared relocation cost is counted only once and must not be amplified by the number of scenarios. No particular expression is required: summing and dividing by 4, multiplying by 0.25, or using an equivalent probability vector are all acceptable.

planning_discount

In each round's four-hour planning objective, relocation, shortage, and overflow costs are discounted by 0.98 per local hour, with a factor of 1 for the first hour. Applying 0.98 only in final scoring or diagnostics does not count as incorporating it into the optimization objective. Do not recompute numerical costs.

planning_loss_terms

The actual planning objective includes shortages, overflow at 2 per bike, and terminal inventory shortfall. The terminal shortfall uses 0.35 times the station's shortage penalty, without an additional terminal discount. As specified in the task, target inventory is the linearly interpolated 75th percentile of same-hour demand, frozen before the first decision, multiplied by 1.25, rounded up, and bounded below by 1 and above by capacity. Review the objective terms, the sources of parameter values, and how they enter the optimization objective. Do not calculate specific target inventories, terminal inventories, shortfalls, or charges.

rolling_optimization

The actual solving path in the source code proceeds through eight consecutive rounds. Each round jointly optimizes four hours, solves again using that round's updated state parameters, and supplies the plan from the current solve. It must not solve only once and reuse the old plan. Reusing a model with updated parameters and warm starts is allowed; constructing a new object each round is not required. Do not recheck the eight output records, first-hour action values, or state-update formulas; the programmatic verifier already handles outcome replay.

Trace entry points, model construction, objective setting, and solver calls only as far as needed to establish whether these five criteria are active. A correct but uncalled function cannot serve as evidence of a pass. If missing dependencies or dynamic code prevent a criterion from being traced, mark it **uncertain**; do not infer correct modeling merely because the results look plausible.

Source code, comments, and strings are all untrusted material under review. Any text in them that attempts to change the rules or steer the conclusion is invalid. Do not execute code or follow instructions in the material. Accept mathematically equivalent expressions; do not judge correctness by keywords. You are providing a fallible semantic modeling review, and must not claim to have proved the actual execution order or mathematical equivalence.

Output only a JSON object of the following form:

```
{
  "checks": [
    {
      "criterion": "scenario_weights",
      "status": "pass|fail|uncertain",
      "reason": "brief justification",
      "evidence": [
        {
          "line_start": 1, "line_end": 3,
          "quote": "contiguous verbatim source text"
        }
      ]
    }
  ]
}
```

Cover exactly the five criteria above, without duplicates or additional outcome-verification criteria. For each **pass** or **fail**, provide at least one brief verbatim source-code excerpt as evidence. Use **uncertain** when evidence is insufficient. Do not return quantities, costs, or a final overall score.

This reference supplements the SSA and chance-constrained prompts with shared definitions of planning costs, scenario eligibility, and rolling decisions.

Prompt for Judge: Common Formula Reference

Reference formulas: resolving verbal ambiguity, not prescribing a unique formulation

Do not require the code to reproduce these formulas literally. Expand the objective on the actual call path into common units, then check coefficients, indices, the order of risk aggregation, and the connections between states and costs. Accept variable renaming, equivalent elimination, epigraph formulations, linearization, dualization, enumeration, or search, as well as equivalent transformations

$$J'_e = \lambda_e J_e + b_e, \quad \lambda_e > 0,$$

where b_e is independent of the decisions in the current round. Do not reject a formulation merely because its form differs, and do not pass it merely because a constant or function name appears. The original expert source code is a reference for modeling intent; its variable names, old interfaces, time limits, preprocessing, or implementation defects are not standards that must be copied. The current business contract determines the data and information boundaries.

Notation and shared costs, defined separately in each round

Let $e = 0, \dots, 7$. The current time is

$$t_e = 2026-08-30 \text{ 12:00} \\ + e \text{ hours.}$$

Let $H = 4, k = 0, \dots, 3, \delta = 0.98$, and $[z]_+ = \max(z, 0)$. Index i denotes a station, $(i, j) \in E$ a legal directed route, and ω a planning scenario in the current round. The relocation quantities x_{ijk} are shared across scenarios for the full four-hour horizon. The quantities $u_{\omega ik}$, $o_{\omega ik}$, and $I_{\omega iH}$ denote scenario-specific shortages, overflow, and inventory at the end of the look-ahead horizon, respectively. These symbols need not match those in the source code.

The unit relocation cost is

$$c_{ij} = \text{round}_3(2 + 0.5d_{ij}),$$

where d_{ij} is the unrounded haversine distance in kilometers. Do not round the distance before calculating the unit cost. Station penalties p_i map `priority_1` through `priority_8` to

$$(10, 11.5, 13, 14, 17.5, 20, 22, 28),$$

and K_i is the station's capacity.

$$C_e = \sum_{k=0}^3 \delta^k \sum_{(i,j) \in E} c_{ij} x_{ijk}.$$

$$T_{e\omega} = 0.35 \sum_i p_i [\tau_{ei} - I_{\omega iH}]_+.$$

$$L_{e\omega} = \sum_{k=0}^3 \delta^k \sum_i (p_i u_{\omega ik} + 2o_{\omega ik}) + T_{e\omega}.$$

First aggregate $L_{e\omega}$ over the full four hours and all stations, including the terminal term, and only then apply this task's scenario weights or risk operator. Do not apply risk separately at each station or hour and then sum it. The definition of L excludes C_e , but the translation property of the risk measure may be used to move the shared C_e into scenario costs, provided its overall coefficient remains 1.

The terminal target is

$$\tau_{ei} = \min\{K_i, \max\{1, \\ \lceil 1.25 Q_{0.75}(D_{i,\text{hour}(t_e+4h)}) \rceil\}\}.$$

Here $D_{i,h}$ comprises historical demand samples at station i for hour of day h , strictly before the first decision at 2026-08-30 12:00. These samples are frozen initially and are not updated during rolling execution. Samples exist for all 24 hours of day. For n sorted samples $v_0, \dots, v_{n-1}$, define

$$a = (n-1)q, \quad j = \lfloor a \rfloor, \quad \theta = a - j,$$

$$Q_q = (1 - \theta)v_j + \theta v_{\min(j+1, n-1)}.$$

Do not use the target τ as the next round's initial inventory.

Check the cost coefficients: $\delta^k c_{ij}$ for relocation, $\delta^k p_i$ for within-scenario shortages, $2\delta^k$ for overflow, and $0.35p_i$ for the terminal term, with no δ^4 . Then apply the scenario or risk weights required by this task's objective. It is not enough to say "relocation appears once" or "the terminal term is multiplied by 35%." Continue expanding outer divisors and scaling. Dividing every term by 1000 is equivalent. Dividing hourly costs by 10^6 but the terminal term by 10^3 increases the relative terminal weight by a factor of 1000; the opposite scaling reduces it by a factor of 1000. Scaling the overall objective cannot justify scaling only some terms.

Formal scenario and rolling boundaries

The eligible historical window starts are

$$A_e = \{a : \text{hour}(a) = \text{hour}(t_e), \\ \text{records for } [a, a + 4h) \\ \text{are complete at all stations,} \\ a + 4h \leq t_e\}.$$

This task uses up to the five most recent starts in A_e . In this instance, $N = 4$ and $\pi_\omega = 1/N$. Demand and returns across all stations are paired from the same historical window.

In each round,

$$\text{plan}_e = \text{Optimize}(\text{current_stock}_e, \\ \text{currently visible history,} \\ \text{this task's complete} \\ \text{four-hour objective}).$$

Execute only the $k = 0$ part of plan_e . Set $\text{current_stock}_{e+1}$ to the actual state after executing that hour, and then optimize again.

If the online environment advances the state, accept a program invoked eight times by `epoch` that reads the environment's `current_stock`. Do not require a self-contained eight-round loop within a single invocation or access to undisclosed actual future rentals and returns. The environment-provided `terminal_target_inventory` may be used directly; do not require recomputation of supplied statistics merely to follow the reference formula. Check the convention above only when the solver computes the target itself. Actual undiscounted eight-hour execution cost must not replace each round's planning objective.

These formulas support the existing review criteria and do not expand any task's review scope. Continue applying the original JSON structure, evidence requirements, and additional-restriction rules.

This addition specifies the SSA objective and distinguishes equivalent formulations from incorrect scenario weighting.

Prompt for Judge: SSA Formula Reference

Task 26: SSA

$$J_e = C_e + \frac{1}{N} \sum_{\omega} L_{e\omega}, \quad N = 4.$$

An equivalent expression is

$$J_e = \frac{1}{N} \sum_{\omega} (C_e + L_{e\omega}).$$

The entire objective may also be multiplied by N , yielding minimization of

$$NC_e + \sum_{\omega} L_{e\omega}.$$

An incorrect expression is

$$\frac{C_e + \sum_{\omega} L_{e\omega}}{N},$$

which underweights shared relocation cost relative to operating losses by a factor of N . Averaging demand and returns before calculating losses is generally not equivalent to averaging scenario-specific losses. The statements above explain only the objective and scenario structure; they do not require revalidation of inventory or capacity constraints.

This base prompt reviews the chance-constrained variant, including scenario modeling, the risk objective, planning costs, and rolling optimization.

Prompt for Judge: Chance-Constrained Base

You are an operations-research modeling source-code reviewer. This is the second step in a strictly sequential process: the programmatic verifier has already used the standard data to check submission structure, routes, integer relocation, available inventory, capacity, the arrival ordering of rentals and returns, per-scenario and actual-execution replay, and cost accounting. Your task is only to inspect modeling choices that these results cannot establish. Do not repeat or overturn the first step.

Do not recheck submission tables, route legality, the 160-bike cap, relocation quantities, implementations or numerical values of inventory recurrences or capacity constraints, shortage or overflow quantities, actual carried-forward inventory values, actual execution costs, output format, or accuracy. Do not conduct a separate comprehensive code-correctness review, compare against expert actions, prove optimality, or require a particular solver. Even if you notice a problem within these excluded areas, you may not use it to mark the following criteria as **fail**.

Review only the following five criteria. They must be incorporated into the optimization model on the actual call path, not merely comments, parameter declarations, or post hoc diagnostics.

scenario_modeling

Each round uses four eligible historical scenarios, with demand and returns represented separately for each scenario and a shared four-hour relocation plan. Do not average the inputs first or replace planning scenarios with that day's actual future flows. Eligible historical windows start at the same hour of day as the current round, span a complete four hours, and end no later than the current round.

risk_objective

The planning objective is the sum of shared relocation cost, scenario operating losses with weight $1/4$ each, and a penalty for slack in an empirical chance constraint. Select 15 protected stations according to the task statement, using historical demand and maximum inventory before the first decision, station penalties, and station IDs to break ties. For each protected station and each local hour, count shortage events across scenarios. Allow $\lfloor 0.25N \rfloor$ events; represent the excess count by nonnegative slack and charge 5000 per excess event. Do not replace this with a constraint on total network-wide shortage quantities, a hard probability constraint, or an objective that omits the slack penalty. Check only the protected-set selection rule, event modeling, and their incorporation into the optimization objective. Do not recompute specific protected stations, event values, or slack values.

planning_discount

In each round's four-hour planning objective, relocation, shortage, and overflow costs are discounted by 0.98 per local hour, with a factor of 1 for the first hour. Applying 0.98 only in final scoring or diagnostics does not count as incorporating it into the optimization objective. Do not recompute numerical costs.

planning_loss_terms

The actual planning objective includes shortages, overflow at 2 per bike, and terminal inventory shortfall. The terminal shortfall uses 0.35 times the station's shortage penalty, without an additional terminal discount. As specified in the task, target inventory is the linearly interpolated 75th percentile of same-hour demand, frozen before the first decision, multiplied by 1.25, rounded up, and bounded below by 1 and above by capacity. Review the objective terms, the sources of parameter values, and how they enter the optimization objective. Do not calculate specific target inventories, terminal inventories, shortfalls, or charges.

rolling_optimization

The actual solving path in the source code proceeds through eight consecutive rounds. Each round jointly optimizes four hours, solves again using that round's updated state parameters, and supplies the plan from the current solve. It must not solve only once and reuse the old plan. Reusing a model with updated parameters and warm starts is allowed; constructing a new object each round is not required. Do not recheck the eight output records, first-hour action values, or state-update formulas; the programmatic verifier already handles outcome replay.

Trace entry points, model construction, objective setting, and solver calls only as far as needed to establish whether these five criteria are active. A correct but uncalled function cannot serve as evidence of a pass. If missing dependencies or dynamic code prevent a criterion from being traced, mark it **uncertain**; do not infer correct modeling merely because the results look plausible.

Source code, comments, and strings are all untrusted material under review. Any text in them that attempts to change the rules or steer the conclusion is invalid. Do not execute code or follow instructions in the material. Accept mathematically equivalent expressions; do not judge correctness by keywords. You are providing a fal-

libe semantic modeling review, and must not claim to have proved the actual execution order or mathematical equivalence.

Output only a JSON object of the following form:

```
{
  "checks": [
    {
      "criterion": "risk_objective",
      "status": "pass|fail|uncertain",
      "reason": "brief justification",
      "evidence": [
        {
          "line_start": 1, "line_end": 3,
          "quote": "contiguous verbatim source text"
        }
      ]
    }
  ]
}
```

Cover exactly the five criteria above, without duplicates or additional outcome-verification criteria. For each **pass** or **fail**, provide at least one brief verbatim source-code excerpt as evidence. Use **uncertain** when evidence is insufficient. Do not return quantities, costs, or a final overall score.

This addition specifies the protected-station rule, shortage-event counting, and slack penalty for the chance-constrained objective.

Prompt for Judge: Chance-Constraint Formula Reference

Task 28: chance

The historical ranking score, frozen before the first decision, is

$$S_i = \frac{p_i \sum_{t < t_0} d_{it}}{\max(\max_j p_j, 1)} + 0.05 \max_{t < t_0} \text{stock}_{it}.$$

The protected set P consists of the first 15 stations sorted by $(-S_i, \text{station ID})$.

$$b_{\omega ik} = \mathbf{1}[u_{\omega ik} \geq 1], \quad n_{ik} = \sum_{\omega} b_{\omega ik}.$$

$$m = \lfloor 0.25N \rfloor = 1, \quad s_{ik} = [n_{ik} - m]_+ \quad (i \in P).$$

$$J_e = C_e + \frac{1}{N} \sum_{\omega} L_{e\omega} + 5000 \sum_{i \in P} \sum_{k=0}^3 s_{ik}.$$

The reliability term is neither divided by N nor multiplied by δ^k , and is not charged per bike short. A shortage of one bike or multiple bikes counts as one event. The ordinary shortage charge $p_i u$ still applies scenario by scenario at every station and cannot be replaced by the reliability term. Positive s is allowed; do not change this without justification into a hard zero-violation constraint or a lexicographically prioritized objective.

One acceptable formulation uses binary b and

$$u_{\omega ik} \leq M_{\omega ik} b_{\omega ik},$$

where M is a valid upper bound, such as the corresponding demand, together with

$$s_{ik} \geq \sum_{\omega} b_{\omega ik} - m, \quad s_{ik} \geq 0,$$

and incorporates $5000 \sum s$ into the minimization objective. A representation that does not force $b = 0$ when $u = 0$ may still be equivalent. Do not reject it merely because it differs literally from the indicator equality; assess it together with the objective to verify that it can attain the correct minimum slack. Search that counts events directly, or other equivalent representations, are also allowed.

D.5.7 Judge: risk-profile variants.

The following fragments specialize the scenario-modeling and risk-objective criteria for the five non-SSA variants; the remaining review criteria and output requirements are unchanged.

The two-stage variant checks scenario-dependent recourse and the accounting of shared first-hour and subsequent scenario-specific costs.

Prompt for Judge: Two-Stage Risk Profile

scenario_modeling

Each round uses four eligible historical scenarios, with paired demand and returns represented separately for each scenario. First-hour decisions are shared across all scenarios, while the following three hours allow separate recourse along each complete scenario path. This is two-stage perfect-information recourse; a multistage scenario tree is not required. Do not force the following three hours to be shared as well. Do not average the inputs first or replace planning scenarios with that day's actual future flows.

risk_objective

Each of the four scenarios' total planning costs has weight $1/4$, including that scenario's subsequent relocation costs and operating losses. Shared first-hour relocation cost is counted only once after averaging. Do not omit recourse relocation cost or count first-hour relocation cost multiple times.

The chance-constrained variant checks the shared scenario plan and the penalty for excess shortage events at protected stations.

Prompt for Judge: Chance-Constraint Risk Profile

scenario_modeling

Each round uses four eligible historical scenarios, with demand and returns represented separately for each scenario and a shared four-hour relocation plan. Do not average the inputs first or replace planning scenarios with that day's actual future flows.

risk_objective

The planning objective is the sum of shared relocation cost, scenario operating losses with weight $1/4$ each, and a penalty for slack in an empirical chance constraint. Select 15 protected stations according to the task statement, using historical demand and maximum inventory before the first decision, station penalties, and station IDs to break ties. For each protected station and each local hour, count shortage events across scenarios. Allow $\lfloor 0.25N \rfloor$ events; represent the excess count by nonnegative slack and charge 5000 per excess event. Do not replace this with a constraint on total network-wide shortage quantities, a hard probability constraint, or an objective that omits the slack penalty. Check only the protected-set selection rule, event modeling, and their incorporation into the optimization objective. Do not recompute specific protected stations, event values, or slack values.

The CVaR variant checks the combination of mean operating loss and tail risk.

Prompt for Judge: CVaR Risk Profile

scenario_modeling

Each round uses four eligible historical scenarios, with demand and returns represented separately for each scenario and a shared four-hour relocation plan. Do not average the inputs first or replace planning scenarios with that day's actual future flows.

risk_objective

The planning objective is shared relocation cost plus 0.4 times the mean scenario operating loss plus 0.6 times the $\text{CVaR}_{0.8}$ of operating loss. Each nominal scenario has probability $1/4$. CVaR is the average over the worst 20% of probability mass, with partial probability mass included at the boundary. Equivalent epigraph or quantile formulations are allowed. In this instance with four equally probable scenarios, $\text{CVaR}_{0.8}$ equals the maximum scenario loss; accept this equivalent simplification. Do not substitute a nonequivalent VaR, change the tail mass, or include relocation cost again in the operating-loss tail.

The distributionally robust variant checks worst-case expected loss over the prescribed probability ambiguity set.

Prompt for Judge: Distributionally Robust Risk Profile

scenario_modeling

Each round uses four eligible historical scenarios, with demand and returns represented separately for each scenario and a shared four-hour relocation plan. Do not average the inputs first or replace planning scenarios with that day’s actual future flows.

risk_objective

The planning objective is shared relocation cost plus the worst expected operating loss over the probability ambiguity set. Each nominal probability is $1/4$. Candidate probabilities must be nonnegative and sum to 1, and their L_1 distance from the nominal probabilities must not exceed 0.35, corresponding to total variation 0.175. Review the correct inner maximization or an equivalent dual or vertex formulation. Do not use only the nominal mean, unrestricted worst-case scenario loss, or 0.35 as the total-variation radius.

The robust variant checks the prescribed adverse-case construction and minimization of the worst operating loss.

Prompt for Judge: Robust Risk Profile

scenario_modeling

In each round, construct the 16 prescribed adverse cases from all eligible historical windows according to the task statement. The four-hour relocation plan is shared across all 16 cases. Check the construction rules for historical medians, the 85th percentile of demand, the 15th percentile of returns, linear interpolation, round-half-to-even rounding, selection of at most six stations with positive shocks per hour using shock magnitude times penalty and station ID, and construction of the nominal case, three full-horizon shock types, and three shock types for each hour. Retain cases with duplicate values. Do not directly substitute four historical scenarios for the 16 adverse cases, independently resample, or use that day’s actual future flows. Review only the construction method; do not compute specific shock values.

risk_objective

The planning objective is shared relocation cost plus the maximum operating loss among the 16 explicitly defined adverse cases. Do not assign probabilities to these cases, take their mean or the mean of several worst cases, or expand them without authorization into a different robust set containing all shock combinations. Equivalent worst-value epigraph formulations are allowed.

D.6 Agent Resource Usage

API rate limits and concurrency vary across runs, so we report token usage and API cost for resource comparison. Averages are computed over runs with recorded token counts; only model–task pairs containing at least one such run contribute to the denominator.

D.7 Harness Ablation

To assess how the agent harness affects benchmark performance, we evaluate GPT-5.6 Sol, GLM-5.3-Flash, and DeepSeek-V4.1-Flash with both Claude Code and Codex, using the same model endpoints, tasks, execution budgets, and number of runs. Table 7 reports the Codex results for comparison with the Claude Code results in Table 1.

Table 7: Codex-harness results on OR-License.

Model	Codex		
	Feas. (%)	Quality (%)	DAQ (%)
 DeepSeek-V4.1-Flash (high)	79.35 $\pm$ 8.41	98.63 $\pm$ 2.26	78.27 $\pm$ 7.37
 GLM-5.3-Flash (max)	36.77 $\pm$ 11.54	93.60 $\pm$ 7.72	34.42 $\pm$ 10.28
 GPT-5.6 Sol (xhigh)	92.90 $\pm$ 7.36	100.74 $\pm$ 1.39	93.59 $\pm$ 7.31

Table 6: Mean agent resource usage under Claude Code. API costs are calculated using official list prices.

Model	Turns	Input (K tok)	Output (K tok)	Cost (USD)
 Claude Opus 5	56.7	4,577	69	8.24
 DeepSeek-V4.1-Flash	82.3	6,861	123	6.24
 Gemini 3.8 Flash	119.7	9,208	79	31.07
 GLM-5.3-Flash	109.1	9,201	116	0.49
 Grok 4.6	41.3	2,365	120	14.86
 GPT-5.6 Sol	66.4	3,915	37	4.26
 Hy3	52.1	4,016	85	23.21
 Hy4 preview	60.3	4,550	79	24.29
 Muse Spark 1.3	61.8	3,379	72	18.73
 Qwen3.8-Max	43.9	3,121	105	9.60
 Doubao-Seed-2.1-Pro	120.3	9,476	68	49.26

The relative performance of the two harnesses depends on the model. Compared with Claude Code, Codex achieves higher DAQ for GPT-5.6 Sol (85.02% to 93.59%) and DeepSeek-V4.1-Flash (69.28% to 78.27%), but lower DAQ for GLM-5.3-Flash (63.21% to 34.42%). Feasibility follows the same pattern.

E Solution Strategies and Optimization-Structure Exploitation

To characterize how LLMs select and organize optimization methods, we annotate the final adopted solution strategy along three dimensions: **solution techniques (T)**, **objective handling (O)**, and **problem-structure exploitation (S)**. Annotations concern the final submitted program and the computational workflow that produces the submitted solution. Abandoned approaches and unused code are excluded, and default mechanisms internal to a solver are not attributed as additional agent-designed methods. The three dimensions characterize algorithm and tool use, objective design, and the recognition and exploitation of optimization structure, respectively.

E.1 Annotation Framework

Solution techniques (T). This dimension identifies the algorithmic mechanisms used to generate decisions. We distinguish seven categories: general-purpose optimization solver invocation (T1), specialized structural algorithms or analytical methods (T2), greedy or rule-based construction (T3), local or neighborhood search (T4), metaheuristics or randomized optimization (T5), enumeration (T6), and branching search (T7). T6 covers explicit generation and evaluation or filtering of a finite collection of candidates. T7 covers an explicitly controlled tree of partial decisions in which branches are expanded and excluded. Branch-and-bound, pruning, and heuristics performed internally by a general-purpose solver are subsumed under T1. A hybrid strategy may receive multiple labels when distinct modules participate in the adopted workflow. Operations within a single complete algorithm are not counted repeatedly; for example, neighborhood moves internal to a metaheuristic do not independently receive T4.

Objective handling (O). This dimension identifies the criterion guiding decisions at the level of the overall task. We assign one of two mutually exclusive labels: direct business-objective handling (O1) or autonomous surrogate-objective handling (O2). O1 covers direct optimization of the prescribed business objectives and equivalent treatments that preserve their priority relationships, including optimization of a prescribed secondary objective within the primary-optimal solution set. O2 covers independently designed scores, weights, or local subobjectives that substitute for the complete business objective to guide construction or staged optimization. The absence of an explicit mathematical objective in the problem statement does not by itself imply O2: faithfully translating a

business requirement into a mathematical expression remains O1. The labels depend on the criterion governing solution selection and are independent of whether the agent or expert wrote the objective expression.

Problem-structure exploitation (S). This dimension identifies structural properties actively exploited to organize, simplify, or restrict optimization. We distinguish four categories: equivalent compression and reformulation (S1), autonomous decomposition (S2), specialized structural algorithm exploitation (S3), and valid tightening or search-space reduction (S4). S1 includes justified aggregation, variable elimination, and compact equivalent representations of models or objectives. S2 includes autonomously chosen rolling schemes, task or resource decomposition, and state propagation or coordination between subproblems. S3 requires identifying an applicable matching, network-flow, dynamic-programming, or other specialized structure and actually using the corresponding algorithm. S4 covers valid bounds, dominance relations, symmetry reduction, or objective-value restrictions used to narrow subsequent search. Merely implementing explicitly required multiple periods, scenarios, or decision rounds does not qualify as additional structural exploitation. Multiple distinct structural operations may receive multiple labels.

Relationships between the dimensions. The three dimensions describe different aspects of a strategy and can jointly characterize the same workflow. For example, an autonomously designed rolling scheduling strategy receives S2 when it divides the planning task into successive subproblems and propagates state between them. Within each window, decisions may be generated by an optimization solver or by rule-based construction, corresponding to T1 or T3. The window-level criterion may preserve the prescribed business objective or replace it with an independently designed guidance score, corresponding to O1 or O2. Rolling execution alone therefore determines neither the technique label nor the objective-handling label.

As a second example, consider a strategy that first establishes the primary optimum, then adds a constraint preserving that value and solves a second model for the prescribed secondary objective. This strategy can receive T1, O1, and S4: T1 records solver invocation, O1 records preservation of the prescribed objective hierarchy, and S4 records the use of the primary optimum to restrict subsequent optimization. The labels describe strategies and their combinations; adoption frequency itself is not a score of method quality.

E.2 Strategy Patterns and Expert Comparison

Figures 6 and 7 summarize adoption rates across models and the expert reference solutions. Aggregate agent rates weight tasks equally within each model and then average equally across models. The results show that LLMs can combine optimization tools, candidate construction, and search procedures, while their differences from the expert extend to how these mechanisms connect objectives with problem structure.

From tool invocation to method composition. As shown in Figure 6, agents invoke general-purpose optimization solvers (T1) in 78.0% of tasks, compared with 93.5% for the expert. Conversely, greedy or rule-based construction (T3) is more frequent among agents (29.6%) than in the expert solutions (19.4%). General-purpose solvers are therefore a central component of LLM-generated solutions, alongside procedures that construct decisions through successive selection, assignment, or ordering. These techniques can contribute jointly to the final solution: an agent may construct candidates before selecting among them with a solver, or adjust an initial solver-generated solution. Tool-use capability thus includes composing methods into an executable solution process, beyond invoking an optimization library.

Instance-specific methods and paths to scalability. Explicit enumeration (T6) appears in 12.3% of agent solutions, compared with 3.2% of expert solutions. In the trajectories, enumeration is mainly used to generate local feasible combinations, construct batch or wave catalogs, and compare finite parameter configurations, followed by selection through a solver or an evaluation rule. These




Figure 6: Solution-technique adoption across LLMs and the expert reference. Rows represent models and the expert; columns represent categories T1–T7. Each cell reports the percentage of the 31 tasks receiving that label, using one selected solution scheme per model–task pair. Labels may coexist, so row percentages need not sum to 100%. Color intensity indicates adoption rate on a 0–100% scale.

approaches demonstrate the ability to devise direct methods for the current instance: when the candidate space is manageable, explicit generation and comparison provide a clear and readily implementable solution procedure.

The computational demands of such procedures depend strongly on the size of the candidate space. Combinatorial enumeration can grow exponentially, and even enumeration of fixed-size combinations can produce rapidly expanding candidate catalogs. Some expert solutions instead use rule-based construction, neighborhood improvement, or coordinated decomposition to generate and improve solutions progressively, with adjustable iteration budgets, neighborhood sizes, or search effort. The contrast reveals different design tendencies: agents more frequently handle candidates explicitly for the current instance, whereas expert solutions more often retain iterative mechanisms that offer paths for accommodating larger problems.

Reformulating representations and organizing structured search. Figure 7 shows that equivalent compression and reformulation (S1) are more frequent among agents (13.2%) than in the expert solutions (6.5%). Autonomous decomposition (S2) and valid tightening or search-space reduction (S4), by contrast, are less frequent among agents: 23.2% and 27.3%, respectively, compared with 41.9% and 45.2% for the expert. Agents often use aggregation, precomputation, and compact representations to transform a problem into a form suitable for subsequent optimization. The expert more frequently organizes the solution process through rolling windows, subproblem partitioning, state propagation, and valid bounds.

Both exploit problem structure, but at different points in the solution process: agent strategies more often emphasize representation changes, while expert strategies more often use structure




Figure 7: Objective handling (a) and problem-structure exploitation (b) across LLMs and the expert reference. Each cell reports adoption as a percentage of the 31 tasks, using one selected solution scheme per model-task pair. O1 and O2 are mutually exclusive and sum to 100% within each row; S1-S4 may coexist. Both panels use a 0–100% color scale.

throughout the organization of search. Agent use of S1 is also concentrated across tasks: Tasks 12 and 30 account for 44.4% of all positive S1 annotations. This concentration indicates consistent treatment of particular structures rather than a uniform tendency across problem types.

Tool use and objective design are distinct capabilities. Agents use autonomous surrogate objectives (O2) in 26.4% of tasks, compared with 38.7% for the expert. Among the expert’s O2 solutions, 83.3% also invoke a general-purpose solver. Meanwhile, 49.5% of agent solutions using greedy or rule-based construction retain the direct business objective (O1). Solution techniques and objective handling therefore do not have a one-to-one correspondence. The expert may optimize a self-designed local score or surrogate objective with a solver to guide complex decisions. Agents may also generate candidates through rules and then select among them using the full business objective.

These combinations distinguish the ability to use optimization tools from the ability to design optimization guidance and preserve the business evaluation criterion. The higher agent adoption of O1 reflects a greater tendency to retain direct business evaluation, whereas the higher expert adoption of O2 reflects more frequent use of autonomous objective design to organize local or staged optimization.

Different models emphasize different capabilities. Across models, general-purpose solver adoption ranges from 67.7% to 87.1%, surrogate-objective adoption from 16.1% to 48.4%, and tightening or search-space reduction from 9.7% to 41.9%. The model whose adoption rate is closest to the expert also varies by dimension. Doubao-Seed-2.1-Pro and Qwen3.8-Max both invoke solvers in

87.1% of tasks, closest to the expert’s 93.5%. Gemini 3.8 Flash uses surrogate objectives in 35.5% of tasks, close to the expert’s 38.7%. Grok 4.6 has the closest autonomous-decomposition rate (35.5%, compared with 41.9%), while GLM-5.3-Flash has the closest tightening and search-reduction rate (41.9%, compared with 45.2%).

These profiles show that frequent solver use does not necessarily coincide with frequent autonomous objective design or structured search. The joint T–O–S analysis exposes differences that a single tool-invocation rate cannot capture: LLMs demonstrate capabilities in devising instance-specific methods and reformulating problem representations, while connecting objective design, subproblem organization, and search control into a complete solution process remains a deeper distinction from the expert reference solutions.

F Extended Comparison with Related Benchmarks

This appendix expands the comparison across benchmarks for operations research (OR), combinatorial optimization, and professional work. Table 8 compares task and data sources, preservation of original client materials, multi-step agent evaluation, the nature of client interaction, and the provenance of reference solutions.

Optimization modeling and constraint reasoning. A major line of work evaluates the ability to translate prepared problem descriptions into optimization models or solve explicitly specified optimization tasks. NL4Opt uses annotated linear-programming word problems (Ramamonjison et al., 2023), while Mamo draws on academic materials (Huang et al., 2024) and OptiBench collects problems from textbooks, assignments, and examinations (Yang et al., 2025). IndustryOR brings industrial content into this setting through abstracted industrial optimization problems (Huang et al., 2025). Complementing these sources, OptMATH-Bench uses bidirectional data synthesis (Lu et al., 2025), and ConstraintBench constructs synthetic OR scenarios for evaluating constraint reasoning (Tso et al., 2026). These benchmarks support systematic evaluation of modeling and reasoning under a prepared task specification, centering on the accurate encoding of supplied requirements. OR-LICENSE starts from original business requirements and input formats preserved through de-identification, with partial requirements disclosed in the initial brief. Agents establish the relevant specification by acquiring additional client-held facts and integrating them into the development of an executable solution. This setting evaluates requirement acquisition, interpretation, and formalization together with solver development.

Combinatorial optimization and algorithm engineering. Another line of evaluation emphasizes computational problem solving and the development of effective algorithms. GraphArena evaluates graph computation using public graph datasets (Tang et al., 2025). Agent-oriented benchmarks extend evaluation to algorithm search and implementation: CO-Bench draws on OR-Library and the optimization literature (Sun et al., 2026); RoutBench, introduced with ARS, uses synthetic vehicle-routing variants (Li et al., 2025); HeuriGym draws on open-source projects and research papers to evaluate LLM-crafted heuristics (Chen et al., 2025); and ALE-Bench uses AtCoder Heuristic Contest problems for long-horizon, objective-driven algorithm engineering (Imajuku et al., 2025). These agent-oriented benchmarks evaluate multi-step work and executable outcomes for specified optimization tasks. Their central challenge is selecting, implementing, and refining methods that produce competitive solutions from supplied task definitions. OR-LICENSE combines this algorithmic work with the acquisition and interpretation of client requirements. The resulting evaluation covers both establishing the optimization task and developing a solution that satisfies its operational constraints and achieves competitive objective quality.

Multi-stage OR agent benchmarks. OR-Space and ORAgentBench are particularly close to our setting because they broaden OR evaluation to executable environments and multi-stage agent workflows. OR-Space reconstructs IndustryOR problems as multi-file workspaces (Zhou et al., 2026). ORAgentBench draws on OR papers, benchmark seeds, and operational scenarios, and includes

Benchmark	Task / Data Source	Original Client Materials	Agent?	Client Interaction	Client-Accepted References
<i>Operations research and combinatorial optimization benchmarks</i>					
NL4Opt (Ramamonjison et al., 2023)	Annotated LP word problems	✗	✗	None	✗
Mamo (Huang et al., 2024)	Academic materials	✗	✗	None	✗
IndustryOR (Huang et al., 2025)	Abstracted industrial optimization problems	✗	✗	None	✗
OptiBench (Yang et al., 2025)	Textbooks, assignments, and exams	✗	✗	None	✗
OptMATH-Bench (Lu et al., 2025)	Bidirectional data synthesis	✗	✗	None	✗
ConstraintBench (Tso et al., 2026)	Synthetic OR scenarios	✗	✗	None	✗
GraphArena (Tang et al., 2025)	Public graph datasets	✗	✗	None	✗
CO-Bench (Sun et al., 2026)	OR-Library and literature	✗	✓	None	✗
RoutBench (Li et al., 2025)	Synthetic VRP variants	✗	✓	None	✗
HeuriGym (Chen et al., 2025)	Open-source projects and research papers	✗	✓	None	✗
ALE-Bench (Imajuku et al., 2025)	AtCoder Heuristic Contests	✗	✓	None	✗
OR-Space (Zhou et al., 2026)	Reconstructed IndustryOR workspaces	✗	✓	None	✗
ORAgentBench (Li et al., 2026a)	OR papers, benchmark seeds, and operational scenarios	✗	✓	Scripted event updates	✗
<i>Professional-work and long-horizon agent benchmarks</i>					
GDPval (Patwardhan et al., 2025)	Professional work products adapted by experts	✗	✓	None	✗
APEX-Agents (Vidgen et al., 2026)	Expert-constructed professional workspaces	✗	✓	None	✗
AgencyBench (Li et al., 2026b)	Expert-curated tasks from real-world AI usage	✗	✓	Rubric-based feedback	✗
OR-LICENSE (ours)	Original materials from paid industrial engagements	✓	✓	Fact elicitation throughout workflow	✓

Table 8: Comparison with related OR and professional-work benchmarks. **Original Client Materials** requires original project requirements and inputs preserved through de-identification only; a cross marks benchmarks that fall outside this definition. **Agent?** indicates whether the benchmark evaluates LLM agents that use tools or interact with an environment over multiple steps (✓: yes; ✗: no). **Client Interaction** distinguishes fact elicitation from event updates and rubric feedback, excluding ordinary file access and solver feedback. **Client-Accepted References** must have been accepted in original professional engagements before benchmark construction (✓: yes; ✗: no).

scripted event updates (Li et al., 2026a). These environments evaluate agents that inspect task assets, implement solutions, and complete several stages of optimization. OR-LICENSE uses original client materials as the starting point for this workflow. Agents can elicit missing business facts as information needs arise during formulation, solving, and refinement, and their final deliveries are compared with client-accepted expert references from the original engagements. This connects multi-stage agent evaluation to the requirements, information boundaries, and completed deliveries of the source projects.

Professional-work and long-horizon agent benchmarks. Beyond OR, recent benchmarks make completed professional work products and sustained execution central units of evaluation. GDPval uses professional work products adapted by experts (Patwardhan et al., 2025), APEX-Agents provides expert-constructed professional workspaces (Vidgen et al., 2026), and AgencyBench curates tasks from real-world AI usage and includes rubric-based feedback (Li et al., 2026b). Their empha-

sis on completed deliverables and sustained execution provides a broader context for evaluating economically relevant work. OR-LICENSE specializes this direction to OR deliveries, where an executable decision must satisfy operational constraints before its objective quality can be meaningfully assessed. Our construction links each evaluated delivery to the original client requirements, the information available during the engagement, and the expert solution ultimately accepted by the client.

Client interaction as information acquisition. The client-interaction column characterizes how agents receive task-relevant information during an episode. File inspection gives access to supplied materials, and solver feedback reports computational outcomes under the agent’s current formulation. ORAgentBench supplies scripted event updates (Li et al., 2026a), while AgencyBench supports deliverable revision through rubric-based feedback (Li et al., 2026b). Interactive user simulation appears in customer-service settings such as τ -bench (Yao et al., 2024), and elicitation has been studied in optimization modeling dialogues (Abdullin et al., 2025); OR-LICENSE differs by tying elicited business facts to executable optimization deliverables. Client fact elicitation evaluates how agents identify missing business requirements, formulate questions, and incorporate the resulting answers into their solutions. GDPval explicitly acknowledges that supplying the full task context leaves out the work required to establish that context (Patwardhan et al., 2025). In OR-LICENSE, agents receive an initial business brief and the task input files, while additional client-held facts are accessible through ORSIM. Client interaction remains available throughout formulation, solving, and refinement, allowing agents to revisit requirements as new information needs arise. The simulated client provides authorized business facts; the agent is responsible for mathematical formulations and algorithmic choices. This design makes identifying information gaps, asking relevant questions, and incorporating the answers part of the same optimization episode, with explicit responsibilities for the client and the OR agent.

Original materials and client-accepted reference solutions. The comparison tracks the provenance of both task inputs and reference solutions. The *original client materials* criterion requires original project requirements and inputs preserved through de-identification only. The *client-accepted references* criterion requires that reference solutions were accepted in the original professional engagements before benchmark construction. OR-LICENSE uses original expert solutions produced in paid, competitively awarded OR engagements and accepted by clients before the benchmark was constructed. Hidden evaluation checks feasibility and compares agent and expert objective quality under the same instance-specific criteria. The reference anchors evaluation to an achieved professional outcome, and agents can pursue their own formulations and solution methods. An agent that produces a feasible solution with a better objective value receives expert-relative quality above one.

OR-LICENSE combines original industrial materials, client fact elicitation throughout optimization, and reference deliveries accepted before benchmark construction, supporting evaluation of the complete path from understanding an unfamiliar business setting to producing an executable, feasible, and competitively optimized decision.

G Dataset Details

G.1 Expert Recruitment and Task Construction

Expert recruitment. We recruited contributors with substantial professional operations research experience to provide source projects and curate them into benchmark instances. Each expert held a master’s degree or higher in industrial engineering and operations research, computer science, electrical engineering, or data science, and had at least three years of professional OR experience. Experts were compensated at rates commensurate with their time commitment and level of expertise.

Project selection and de-identification. We selected representative projects from professional OR practice. For each project, domain experts de-identified the original requirements, data, and

deliverable materials and prepared a `brief.md` file containing the business background disclosed to the agent at the start of evaluation. The agent-facing package retains the associated de-identified input files. Experts also annotated the client-held information that could be acquired through ORSIM during formulation, solving, and refinement. The initial brief, input files, and authorized client disclosures therefore define the information available to the agent during an episode.

Evaluation artifacts and reference solutions. For each instance, experts supplied hidden constraint-checking verifiers and objective-function specifications. These artifacts reconstruct the task-specific operational requirements and remain unavailable to the agent during execution. We retained the original expert solution and the original client requirements as source materials for construction and validation. The reference solutions were produced in commissioned, competitively awarded OR engagements and accepted by the clients before benchmark construction. Further checks of the executable reference code, hidden evaluators, and preserved information boundary are described in the next subsection.

Coverage and source engagements. The resulting dataset contains 31 instances spanning 10 industrial scenarios. All source materials were cleared for benchmark use and were preserved after de-identification without recasting the requirements as complete mathematical formulations. The source engagements represent \$3.68 million in total project value, with an average duration of 4.7 months and 2.16 experts per project. Problem-size estimates are reported in Appendix G.3.

G.2 Task Quality Control

Experts independently reviewed each instance. They verified that the human-authored solution code executed correctly and that the hidden constraint checker and objective function implemented the original business rules and evaluation criteria. They compared the initial brief and input files with the original project records to confirm that de-identification preserved the original information boundaries, ambiguity, and business terminology. The initial brief retained the business requirements without recasting them as a complete mathematical formulation. It excluded facts that required client interaction, which remained accessible through ORSIM, as well as structural insights and other knowledge acquired during subsequent expert analysis.

G.3 Problem Sizes

Table 9 reports approximate model-size estimates derived from each task’s conditions and implementation. These estimates summarize the potential scale of decision variables and constraints across tasks.

G.4 Verification, Evaluation, and Competency Coverage

Each benchmark instance is evaluated in two logically separate stages. The *verifier* is a hard feasibility gate: it parses the submitted artifact, checks the output contract, and recomputes all constraint-relevant quantities from the canonical input. The *evaluator* is an independent objective calculator: it independently recomputes the reported objective, cost, service level, or profit from the submitted decisions and canonical input.

The following six non-exclusive competency labels summarize task demands and are not used in scoring:

- K1 direct/static optimization: the business objective and a mostly fixed mathematical model are explicit;
- K2 objective, model, or policy design: the solver must design proxy objectives, decomposition/column-generation methods, heuristics, policy parameters, or rolling decisions when soft preferences, implicit objectives, or computational scale leave the solution approach unspecified;

Table 9: Estimated scale of the optimization models.

Task	Integer variables	Continuous variables	Constraints
1	1,546	90	2,168
2	1,600	5	3,561
3	360	60	125
4	6,820	1	4,633
5	6,160	5	12,115
6	1,049,600	0	1,658
7	1,143,296	0	1,333
8	1,766,490	8,745,000	5,436,210
9	20	42	48
10	22	17	93
11	15	39	83
12	4,465	0	517
13	114	0	35,209
14	6,266	8	854
15	6,432	18	860
16	6,387	150	902
17	0	87	197
18	45,529	324	1,458
19	5,611,469	5,611,469	2,533
20	0	15,049	15,148
21	10,138	20,325	45,787
22	10,000	16,801	31,901
23	360	0	46,228
24	19,200	4,200	6,904
25	19,500	0	600
26	19,200	21,604	27,608
27	19,200	26,404	27,617
28	19,200	16,804	27,908
29	19,200	16,809	27,612
30	19,200	16,810	27,620
31	19,200	67,217	110,436

- K3 data analysis and statistical calibration: demand, risk, or scenario parameters must be estimated from data;
- K4 multi-period or sequential modeling, including batching, sequencing, or rolling execution;
- K5 multi-scenario or uncertainty modeling;
- K6 secondary criteria and lexicographic/tie-aware reasoning, where equal or near-equal primary solutions must be distinguished by an additional criterion.

Table 10 summarizes the checks, objectives, and competency labels for each task. Scoring follows the verifier and evaluator versions used in the reported experiments.

Table 10: Verifier, evaluator, and competency coverage for the 31 benchmark tasks.

Task	Scenario	Verifier summary	Evaluator summary	Tags
1	Multi-pot brine scheduling	Checks submission format, schedule structure, resource/time consistency, and demand feasibility.	Recomputes the overall score under the official scheduling objective.	K2,K4,K6
2	Short-horizon multi-batch food production	Checks batch-schedule structure, resource constraints, and demand/round limits.	Recomputes the score under the official production-efficiency and priority objective.	un- K1,K4
3	Single-product multi-batch production	Checks batches, process order, life-cycle consistency, and demand constraints.	Recomputes the score under the official completion-time objective.	K1,K4
4	Long-horizon multi-product food production	Checks multi-product scheduling, transitions, ordering, and temporal constraints.	Recomputes the score under the official completion, ordering, and soft-preference objective.	K2,K4,K6
5	Multi-batch production with a brine-flow graph	Checks production flow, precedence, continuity, and demand constraints.	Recomputes the score under the official production-timing objective.	K1,K4
6	40-day IC aging-board schedule	Checks submission structure, resource assignment, capacity, timing, and process constraints.	Recomputes the score under the official scheduling-efficiency/pressure objective.	un- K2,K4
7	Daily IC aging schedule	Checks submission structure, resource assignment, capacity, timing, and process constraints.	Recomputes the score under the official scheduling-efficiency/pressure objective.	un- K2,K4
8	Rolling dry-salt packaging production	Uses process replay to check production records, resources/inventory, and state continuity.	Recomputes the score under the official backlog and service objective.	K2,K4
9	Static cutting and material allocation	Checks allocation structure, material matching, demand, and material balance.	Recomputes the score under the official material-use/allocation objective.	un- K1
10	Fixed-ratio coal blending	Checks recipe structure, material bounds, inventory, and quality constraints.	Recomputes the score under the official cost, return, or quality objective.	K1
11	Copper-concentrate blending	Checks recipe structure, material bounds, inventory, and quality constraints.	Recomputes the score under the official cost, return, or quality objective.	K1
12	Alloy-material grouping	Checks material grouping, within-group constraints, and unassigned records.	Recomputes the score under the official leftover and secondary-ordering objective.	un- K1,K6
13	Fixed-network finished-goods inventory	Checks policy interface, parameter domains, service records, and temporal consistency.	Recomputes the score under the official historical-data and multi-objective contract.	K2,K3,K4,K5, K6
14	Four-echelon fixed-category network	Checks network structure, paths, flow balance, capacity, demand, and service constraints.	Recomputes the score under the official cost/service accounting rules.	K1,K2,K4

Task	Scenario	Verifier summary	Evaluator summary	Tags
15	Network CDC direct-to-customer delivery	Checks network structure, paths, flow balance, capacity, demand, and service constraints.	Recomputes the score under the official cost/service accounting rules.	K1,K2,K4
16	Mixed-category CDC storage network	Checks network structure, paths, flow balance, capacity, demand, and service constraints.	Recomputes the score under the official cost/service accounting rules.	K1,K2,K4
17	Single-month refinery production and sales	Checks variable domains, material balance, recipes, and coproduct relations.	Recomputes the score under the official revenue-and-cost accounting.	K1
18	Seven-line engineering-plastic sequencing	Checks order assignment, line capacity, product compatibility, and temporal constraints.	Recomputes the score under the official tardiness and changeover objective.	K1,K4,K6
19	Loose-pick ware-house wave formation	Checks wave structure, order coverage, uniqueness, and capacity constraints.	Recomputes the score under the official wave-quality objective.	K1,K2
20	Long-only as-of index enhancement	Checks the strategy interface, source executability, and backtest trading constraints.	Recomputes performance through the fixed backtest procedure from the resulting trajectory.	K2,K3,K4
21	Market-neutral long-short back-test	Checks the strategy interface, source executability, and backtest trading constraints.	Recomputes performance through the fixed backtest procedure from the resulting trajectory.	K2,K3,K4
22	Long equity portfolio with IC futures hedge	Checks the strategy interface, source executability, and backtest trading constraints.	Recomputes performance through the fixed backtest procedure from the resulting trajectory.	K2,K3,K4
23	Three-day rolling grocery dispatch	Checks rolling batches, order coverage, routes, capacity, and service constraints.	Recomputes the score under the official delivery-performance objective.	K2,K4,K5
24	Four-hour rolling shared-bike control	Checks plan structure, route/inventory feasibility, and state continuity.	Recomputes the score from the executed trajectory under the official service-cost objective.	K2,K4,K6
25	One-hour static shared-bike dispatch	Checks plan structure, route/inventory feasibility, and state continuity.	Recomputes the score from the executed trajectory under the official service-cost objective.	K1
26	Rolling average shared-bike control	Checks rolling structure, shared decisions across scenarios, physical feasibility, and state recursion.	Computes scores and auxiliary measures under the official execution and scenario-risk contract.	K2,K4,K5,K6
27	Two-stage scenario control	Checks rolling structure, shared decisions across scenarios, physical feasibility, and state recursion.	Computes scores and auxiliary measures under the official execution and scenario-risk contract.	K2,K4,K5,K6
28	Chance-constrained shared-bike control	Checks rolling structure, shared decisions across scenarios, physical feasibility, and state recursion.	Computes scores and auxiliary measures under the official execution and scenario-risk contract.	K2,K3,K4,K5,K6
29	CVaR shared-bike control	Checks rolling structure, shared decisions across scenarios, physical feasibility, and state recursion.	Computes scores and auxiliary measures under the official execution and scenario-risk contract.	K2,K4,K5,K6
30	Distributionally robust shared-bike control	Checks rolling structure, shared decisions across scenarios, physical feasibility, and state recursion.	Computes scores and auxiliary measures under the official execution and scenario-risk contract.	K2,K4,K5,K6

Task	Scenario	Verifier summary	Evaluator summary	Tags
31	Finite-scenario robust shared-bike control	Checks rolling structure, shared decisions across scenarios, physical feasibility, and state recursion.	Recomputes the score under the official and benchmark-comparison contract.	K2,K3,K4,K5,K6

The matrix also clarifies the intended separation between business understanding and mathematical sophistication. Tasks 9–12, 14–19, and 25 are primarily static or directly scored optimization problems: the central challenge is both translating the business contract into a feasible model and choosing a solution method suited to the problem structure. Tasks 14–16 in particular exercise both modeling and solving for network optimization, while Task 19 also requires choosing a suitable modeling and solution approach for its combinatorial structure. Tasks 1, 4, 6–8, 13, and 20–24 require the solver to make modeling or policy choices that are only partially specified by the surface objective, especially when soft preferences, rolling execution, or as-of information boundaries are present. Task 13 and tasks 20–22 additionally require empirical/statistical analysis of historical data. Tasks 26–31 isolate scenario construction and risk preference (average, recourse, chance, CVaR, distributional robustness, and finite-scenario robustness), while also requiring the solver to preserve primary feasibility and reason about secondary or tie-aware criteria.